

1U Redundant 850 watts



YH5851-1VAR2A0D

» FEATURES

- 355.0 (L) x 106.0 (W) x 41.5 (H) mm
- N+1 Redundant
- Support PMBus 1.2
- Application for IPC/Storage/Embedded server/Networking
- Redundant Module: YM-2851VAR



» INPUT

Input Voltage	90 - 264VAC
Input Frequency	47-63Hz
Input Current	12.0A max at 115VAC, 6.0A max at 240VAC
Inrush Current	60A max at 264VAC
Power Factor	0.95 at 115VAC / 60Hz, 0.95 at 230V / 50Hz
Earth Leakage Current	3.5mA max at 240VAC / 50Hz

» GENERAL


Efficiency	80 Plus PLATINUM certified, Highest efficiency 94% at 230VAC
Power Density	8.92 W/in ³
MTBF	100 kHrs per Bellcore TR-332 ISSUE1 at 25°C ambient

» ENVIRONMENTAL

Operating Temperature	-5 to 50°C
Operating Humidity	85% RH, Non-condensing
Storage Temperature	-40°C to +70 °C
Operating Altitude	Sea level to 5,000 m
Shock Operating	10G, no malfunction
Non-Operating	0.02G ² /Hz form 20Hz to 1KHz
Vibration Operating	0.01G ² /Hz at 10Hz, 0.02G ² /Hz at 20Hz

» EMC & SAFETY

Emissions	EN55022, class A Conducted EN55022, class A Radiated
Harmonic Currents	EN61000-3-2
Voltage Flicker	EN61000-3-3
EFT/Burst	EN61000-4-4
Surge	EN61000-4-5
Conducted Immunity	EN61000-4-6
Safety Approvals	UL/cUL, TUV, CB, CE, CCC, FCC, BSMI



Output	Minimum Load	Maximum Load	Condition	Ripple & Noise
+3.3V	1.5A	20A	+3.3V ~ +5V combined power ≤ 140W	50mV p-p
+5V	1.0A	20A		50mV p-p
+12V	1.5A	37A		120mV p-p
-12V	0A	0.5A		120mV p-p
+5VSB	0.1A	3.0A		50mV p-p