



Linears



D48051200A00RH

Input

| | |
|----------------|--|
| Voltage | 230 VAC |
| Line Frequency | 50 Hz |
| Current | 0.150 max. at 120 VAC input |
| Protection | Internal primary current fuse, Inrush limiting |
| Configuration | Wall Mount |

Output

| | |
|---|---|
| Combined Line and Load Voltage Regulation | +/-5% Typical |
| Ripple | 50 mV p-p max. |
| Protection | Output current limiting; short circuit protection |

Safety Approvals

EN60950

Electrical

| | |
|--------------------------|---|
| Topology | Linear/Secondary Switcher - Regulated DC Output |
| Dielectric Withstand EMI | Meets the requirements of EN60950. Complies with EMC Directives |

Environmental

| | |
|-----------------------|---------------------------------|
| Operating Temperature | 5 to 40 deg. C with no derating |
| Storage Temperature | -30 to +85 deg. C |
| Relative Humidity | 5% to 95% non condensing |
| Altitude | 0-10,000 feet |
| Cooling | Convectional - non vented case |

Mechanical

| | |
|---------------------|--|
| Case and Dimensions | 3.3 L x 2.26 W x 1.9 H (in.) 83 L x 56.5 W x 48.5 H (mm) |
| Case Material | GE Noryl SE 100 |
| Weight | 18 ounces; 500 grams |
| Cord and Connector | 6 ft., 2 conductor, 20 AWG cable with Ault #3 connector. . |

7105 Northland Terrace, Minneapolis, MN 55428 USA

TELEPHONE: 763.592.1900 • TOLL FREE: 800.635.3418 • FAX: 763.592.1911

WEB: www.aultinc.com • ©2001 Ault Incorporated