

P28 North American Wall Mount .3-1.4 Watts Series

Features

- 120 VAC Input
- North American Wall Plug Style
- Rated for Continuous Duty
- Filtered
- Unregulated Outputs up to 1.4 Watts
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

Ault Model	Rated Output Volts DC	Maximum Current-Amps	Maximum Watts
P28-030100-A000G	3	0.10	0.3
P28-030200-A000G	3	0.20	0.6
P28-040100-A000G	4	0.10	0.4
P28-040200-A000G	4	0.20	0.8
P28-040250-A000G	4	0.25	1.0
P28-060100-A000G	6	0.10	0.6
P28-060200-A000G	6	0.20	1.2
P28-090100-A000G	9	0.10	0.9
P28-090150-A000G	9	0.15	1.4
P28-120100-A000G	12	0.10	1.2
P28-150100-A000G	15	0.10	1.5
P28-160065-A000G	16	0.06	1.0
P28-160070-A000G	16	0.07	1.1
P28-180050-A000G	18	0.05	0.9
P28-240045-A000G	24	0.05	1.1

Input

- Voltage 120 VAC
- Line Frequency 60 Hz
- Connector North American Wall Plug,
No Ground

Electrical

- Topology DC Unregulated Power
Supply
- Dielectric Withstand 1500 VAC primary -
secondary
1500 VAC primary-core
500 VAC secondary-core
- Protection Energy limiting
- EMI Meets FCC Class B

Safety Approvals

- Safety Agencies UL1310, CSA22.2-223

Environmental

- Operating Temperature 5° to 40° C with no derating
- Storage Temperature -30° to +85° C
- Relative Humidity 5% to 95% non-condensing
- Altitude 0-10,000 feet
- Cooling Convectional - non vented case

Mechanical

- Case Dimensions P28 - North American Wall Plug
2.0 L x 1.4 W x 1.3 H (in)
50 L x 36 W x 32 H (mm)
- Case Material Black 94 V1 Polycarbonate
- Weight 4 ounces, 115 grams,
(excluding cord)
- Cord and Connector 6 ft., 2 Conductor, 24 AWG
Ault #3 Connector
Other Connectors Available

ONE YEAR WARRANTY

Ault Incorporated, 7105 Northland Terrace, Minneapolis, MN 55428

Contact Ault Inc. for all your custom design requirements. Phone: 763.592.1900 · Fax 763.592.1911