

P35 North American Wall Mount .9-3.0 Watt Series

Features

- 120 VAC Input
- North American Wall Plug Style
- Rated for Continuous Duty
- Filtered
- Unregulated Outputs up to 3 Watts
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

Ault Model	Rated Output Volts DC	Maximum Current-Amps	Maximum Watts
P35-050600-A000G	5	0.60	3.0
P35-060500-A000G	6	0.50	3.0
P35-070400-A000G	7	0.40	2.8
P35-080375-A000G	8	0.38	3.0
P35-090200-A000G	9	0.25	2.3
P35-090333-A000G	9	0.33	3.0
P35-100300-A000G	10	0.30	3.0
P35-120100-A000G	12	0.10	1.2
P35-120200-A000G	12	0.20	2.4
P35-120250-A000G	12	0.25	3.0
P35-150200-A000G	15	0.20	3.0
P35-180166-A000G	18	0.17	3.0
P35-210143-A000G	21	0.14	3.0
P35-220136-A000G	22	0.14	3.0
P35-240125-A000G	24	0.13	3.0

Input

- Voltage 120 VAC
- Line Frequency 60 Hz
- Connector North American Wall Plug,
No Ground

Electrical

- Topology DC Unregulated Power
Supply
- Dielectric Withstand 1500 VAC primary -
secondary
1500 VAC primary-core
500 VAC secondary-core
- Protection Current, Thermal or Energy
Limiting
- EMI Meets FCC Class B

Safety Approvals

- Safety Agencies UL1310, CSA22.2-223

Environmental

- Operating Temperature 0° to 40° C with no derating
- Storage Temperature -30° to +85° C
- Relative Humidity 5% to 95% non-condensing
- Altitude 0-10,000 feet
- Cooling Convectional - non vented case

Mechanical

- Case Dimensions P35 - North American Wall Plug
2.3 L x 1.8 W x 1.7 H (in)
59 L x 45 W x 42 H (mm)
- Case Material Black 94 V1 Polycarbonate
- Weight 6 ounces, 175 grams,
(excluding cord)
- Cord and Connector 6 ft., 2 Conductor, 24 AWG
Ault #3 Connector
Other Connectors Available

ONE YEAR WARRANTY

Ault Incorporated, 7105 Northland Terrace, Minneapolis, MN 55428

Contact Ault Inc. for all your custom design requirements. Phone: 763.592.1900 · Fax 763.592.1911