

# P41 North American Wall Mount 3.8-6.0 Watt Series

## Features

- 120 VAC Input
- North American Wall Plug Style
- Rated for Continuous Duty
- Filtered
- Unregulated Outputs up to 6 Watts
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

| Ault Model       | Rated Output<br>Volts DC | Maximum<br>Current-Amps | Maximum<br>Watts |
|------------------|--------------------------|-------------------------|------------------|
| P41-050750-A000G | 5                        | 0.75                    | 3.8              |
| P41-060800-A000G | 6                        | 0.80                    | 4.8              |
| P41-070750-A000G | 7                        | 0.75                    | 5.3              |
| P41-080700-A000G | 8                        | 0.70                    | 5.6              |
| P41-090500-A000G | 9                        | 0.50                    | 4.5              |
| P41-090650-A000G | 9                        | 0.65                    | 5.9              |
| P41-100600-A000G | 10                       | 0.60                    | 6.0              |
| P41-110550-A000G | 11                       | 0.55                    | 6.0              |
| P41-120400-A000G | 12                       | 0.40                    | 4.8              |
| P41-120500-A000G | 12                       | 0.50                    | 6.0              |
| P41-140220-A000G | 14                       | 0.22                    | 3.0              |
| P41-150400-A000G | 15                       | 0.40                    | 6.0              |
| P41-180333-A000G | 18                       | 0.33                    | 6.0              |
| P41-210286-A000G | 21                       | 0.29                    | 6.0              |
| P41-220273-A000G | 22                       | 0.27                    | 6.0              |
| P41-240250-A000G | 24                       | 0.25                    | 6.0              |

### Input

- Voltage 120 VAC
- Line Frequency 60 Hz
- Connector North American Wall Plug, No Ground

### Electrical

- Topology DC Unregulated Power Supply
- Dielectric Withstand 1500 VAC primary - secondary  
1500 VAC primary-core  
500 VAC secondary-core
- Protection Current, Thermal or Energy Limiting
- EMI Meets FCC Class B

### Safety Approvals

- Safety Agencies UL1310, CSA22.2-223

### Environmental

- Operating Temperature 0° to 40° C with no derating
- Storage Temperature -30° to +85° C
- Relative Humidity 5% to 95% non-condensing
- Altitude 0-10,000 feet
- Cooling Convectional - non vented case

### Mechanical

- Case Dimensions P41 - North American Wall Plug  
2.6 L x 2.0 W x 1.6 H (in)  
67 L x 53 W x 41 H (mm)
- Case Material Black 94 V1 Polycarbonate
- Weight 10 ounces, 275 grams, (excluding cord)
- Cord and Connector 6 ft., 2 Conductor, 24 AWG  
Ault #3 Connector  
Other Connectors Available

**ONE YEAR WARRANTY**

**Ault Incorporated, 7105 Northland Terrace, Minneapolis, MN 55428**

**Contact Ault Inc. for all your custom design requirements. Phone: 763.592.1900 · Fax 763.592.1911**