



Linears



P41150150A00RC

Input

Voltage	120 VAC
Line Frequency	60 Hz
Current	0.1A max. at 120 VAC input
Protection	Internal primary current fuse, Inrush limiting
Configuration	Wall Mount

Output

Combined Line and Load Voltage Regulation	+/-5% Typical
Ripple	30 mV p-p max.
Protection	Output current limiting; short circuit protection

Safety Approvals

UL 1310; CSA 22.2-223

Electrical

Topology	Linear - Regulated DC Output
Dielectric Withstand	Meets the requirements of UL 1310; CSA 22.2-223.
EMI	Meets FCC Class B

Environmental

Operating Temperature	5 to 40 deg. C with no derating
Storage Temperature	-30 to +85 deg. C
Relative Humidity	5% to 95% non condensing
Altitude	0-10,000 feet
Cooling	Convectional - non vented case

Mechanical

Case and Dimensions	2.5 L x 2.1 W x 1.6 H (in.) 63 L x 53 W x 41 H (mm)
Case Material	Black 94 V1 Polycarbonate
Weight	10 ounces; 275 grams
Cord and Connector	6 ft., 2 conductor, 22 AWG cable with Ault #3 connector.

7105 Northland Terrace, Minneapolis, MN 55428 USA

TELEPHONE: 763.592.1900 • TOLL FREE: 800.635.3418 • FAX: 763.592.1911

WEB: www.aultinc.com • ©2001 Ault Incorporated