

# P57 North American Wall Mount 14.4-24.0 Watt Series

## Features

- 120 VAC Input
- North American Wall Plug Style
- Rated for Continuous Duty
- Filtered
- Unregulated Outputs up to 24 Watts
- Meets Safety Agency Requirements
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

Ault Model	Rated Output Volts DC	Maximum Current-Amps	Maximum Watts
P57-091667-A000G	9	1.67	15.03
P57-092222-A000G	9	2.22	20.0
P57-121200-A000G	12	1.20	14.4
P57-121500-A000G	12	1.50	18.0
P57-121667-A000G	12	1.67	20.04
P57-181111-A000G	18	1.11	19.98
P57-201000-A000G	20	1.00	20.0
P57-241000-A000G	24	1.00	24.0

## Input

- Voltage 120 VAC
- Line Frequency 60 Hz
- Connector North American Wall Plug, No Ground

## Electrical

- Topology DC Unregulated Power Supply
- Dielectric Withstand 1500 VAC primary - secondary  
1500 VAC primary-core  
500 VAC secondary-core
- Protection Current, Thermal or Energy Limiting
- EMI Meets FCC Class B

## Safety Approvals

- Safety Agencies UL1310, CSA22.2-223

- Operating Temperature 0° to 40° C with no derating
- Storage Temperature -30° to +85° C
- Relative Humidity 5% to 95% non-condensing
- Altitude 0-10,000 feet
- Cooling Convectional - non vented case

## Mechanical

- Case Dimensions P57- North American Wall Plug  
3.4 L x 2.7 W x 2.2 H (in)  
86 L x 69 W x 56 H (mm)
- Case Material Black 94 V1 Polycarbonate
- Weight 27 ounces, 760 grams, (excluding cord)
- Cord and Connector 6 ft., 2 Conductor, 18-20 AWG  
Ault #3 Connector  
Other Connectors Available

## Environmental

**ONE YEAR WARRANTY**

**Ault Incorporated, 7105 Northland Terrace, Minneapolis, MN 55428**

**Contact Ault Inc. for all your custom design requirements. Phone: 763.592.1900 · Fax 763.592.1911**