

AC TO DC EXTERNAL UN-REGULATED WALLMOUNT & DESKTOP ADAPTOR DIVERSE AC PLUGS SINGLE OUTPUT 12.0-15.6 WATTS LINEAR POWER ADAPTORS APS48EA SERIES



FEATURES:

- LOW COST UN-REGULATED ADAPTORS
- WORLDWIDE DIVERSE AC PLUGS
- MEET USA OR EUROPEAN STANDARD
- LOW NOISE LEVEL MEET EMI NORM
- CE MARKING COMPLIANCE

SPECIFICATION

INPUT SPECIFICATION

Input Voltage: Nominal 100/110/120Vac or 220/230/240Vac. Custom Vac available
Input Range: Typical $\pm 8.0\%$
Input Connector: Wallmount Format: WM1,2(USA/Japan)/WM3; (Euro-stecker) / WM4 (Schuko-stecker)/ WM5 (UK)/WM6, 6G(Australia); Desktop Format: PT1,2,3,4,5,6
Input Frequency: 60Hz. for nominal 100/110/120Vac
50Hz for nominal 220/230/240Vac
Input Current: 0.25A @120Vac/60Hz typical
0.15A @ 220 - 240Vac/50Hz typical
Dielectric Withstand: Meets IEC 950


OUTPUT SPECIFICATION

Output Voltage & Current: See Ratings Chart
Output Wattage: Typ.12.5-15.6VA @ 120Vac/60Hz input
Typ. 9.0-12.0VA @ 230Vac/50Hz input
Output Connector: Optional
Noise & Ripple: Typ.20% peak to peak
Overload Protection: None, only by thermal protection
Thermal Protection: Thermal fuse installed in transformer
EMI: Inherent low conducted and radiated noise level, meets EN 55022 & FCC Class B

GENERAL SPECIFICATION

Circuit Topology: Line frequency lamination steel transformer circuit
Safety Standard: UL1950 & CSN C22.2 NO. 950 or IEC 950 Class I & II
Operating Temperature: 0 to +40°C
Storage Temperature: -20 to +85°C
Cooling: Free air convection
Construction: Impact resistant plastic enclosure case
Wallmount & Desktop Format: In EI-48 case

MODEL NO. DESCRIPTION: APS48EA — X X X Y Y Y - N



OUTPUT VOLTAGE/CURRENT RATINGS CHART

U.S.A. VERSION **Input Voltage: 100 ~120Vac/ 0.25A @ 60Hz.**

DEFINED OUTPUT VOLTAGE (Vdc)	OUTPUT VOLTAGE (Vdc) / CURRENT (A)
5.0 Vdc < Any Voltage > 12.0 Vdc	5.0-6.0V/2.5-2.3A, 6.5-7.5V/2.2-2.0A, 8.0-9.0V/1.9-1.7A, 9.5-10.5V/1.6-1.45A, 11.0-12.0V/1.4-1.3A.
12.0Vdc < Any Voltage > 24.0 Vdc	12.5-14.0V/1.24-1.11A, 14.5-15.5V/1.07-1.0A, 16.0-18.0V/0.97-0.86A, 18.5-21.0V/0.84-0.74A, 21.5-23.0V/0.72-0.67A, 23.5-24.0V/0.66-0.65A.

Note: Refer to the upper Chat or consult factory for the exact Model No. and V/A.

SINGLE OUPUT **(Model No. for examples)**

MODEL NO.	AC PLUG	I/P VOLTAGE (Vac)	O/P VOLTAGE (Vdc)	O/P CURRENT (A)
APS48EA-050250-1	WM1	120Vac	5.0V	2.50A
APS48EA-060230-2	WM2	120Vac	6.0V	2.30A
APS48EA-075200-A	A(PT1)	120Vac	7.5V	2.00A
APS48EA-090170-1	WM1	120Vac	9.0V	1.70A
APS48EA-120130-2	WM2	120Vac	12.0V	1.30A
APS48EA-150104-A	A(PT1)	120Vac	15.0V	1.04A
APS48EA-180086-1	WM1	120Vac	18.0V	0.86A
APS48EA-220070-2	WM2	120Vac	22.0V	0.70A
APS48EA-240065-A	A(PT1)	120Vac	24.0V	0.65A

EUROPEAN VERSION **Input Voltage: 220 ~240Vac/0.15A @50Hz.**

DEFINED OUTPUT VOLTAGE (Vdc)	OUTPUT VOLTAGE (Vdc) / CURRENT (A)
5.0 Vdc < Any Voltage > 12.0 Vdc	5.0-6.0V/1.8-1.65A, 6.5-7.5V/1.6-1.4A, 8.0-9.0V/1.35-1.2A, 9.5-10.5V/1.1-1.06A, 11.0-12.0V/1.04-1.0A.
12.0Vdc < Any Voltage > 24.0 Vdc	12.5-15.0V/0.96-0.80A, 15.5-18.0V/0.77-0.66A, 18.5-20.0V/0.64-0.60A, 20.5-22.5V/0.58-0.53A, 23.0-24.0V/0.52-0.50A, 48.0V/0.25A.

Note: Refer to the upper Chat or consult factory for the exact Model No. and V/A.

SINGLE OUPUT **(Model No. for examples)**

MODEL NO.	AC PLUG	I/P VOLTAGE (Vac)	O/P VOLTAGE (Vdc)	O/P CURRENT (A)
APS48EA-050180-3	WM3	220Vac	5.0V	1.80A
APS48EA-060165-4	WM4	220Vac	6.0V	1.65A
APS48EA-075140-5	WM5	240Vac	7.5V	1.40A
APS48EA-120100-6	WM6	240Vac	12.0V	1.00A
APS48EA-150080-3	WM3	220Vac	15.0V	0.80A
APS48EA-180066-4	WM4	220Vac	18.0V	0.66A
APS48EA-240050-5	WM5	240Vac	24.0V	0.50A
APS48EA-480025-6	WM6	240Vac	48.0V	0.25A

MECHANICAL DIMENSIONS: MM [INCHES]

WEIGHT: APS48EA 530g(18.7Oz.)

