






Name
Order number
Switching distance
Mounting

Switch type

Signal Type
Connection

Connection diagramm

KJ1,5-M8EB16-DNS
08313080153
1,5 mm
 shielded
 N.O.
DC NPN
 Cable



M8x1 x 16

Dimension (in mm)
Technical Specification
Operating voltage
Max. ripple
Voltage drop
Max. load current
No load current
Leakage current
Switching frequency
Switching hysteresis
Operating temperature
Temperature drift
Repeat accuracy
Switching state
Short-circuit proof
Overload protection
Reverse voltage protection
Protection category
EMC-level
Housing material
Material active face
Cable length

10 - 30 VDC
 $\leq 10 \%$
2,4 V
200 mA
 $\leq 10 \text{ mA}$
 $\leq 10 \mu\text{A}$
2000 Hz
 $\leq 15 \%$
-25 ° C to 70 ° C
 $\leq 10 \%$
 $\leq 5 \%$
LED
yes
yes
yes
IP67
DIN EN 60947-5-2:2008
Stainless steel V2A
PBT
2 m



KJ1,5-M8EB16-DNS

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Utilisation category
Cable material
Cable cross
Termination

DC13
PVC
3x0.14 mm²
2m PVC 3x0.14mm²

Errors and omissions exceptet