





Name
Order number
Switching distance
Mounting

KJ4-Q15KN32-DPÖ
08313150420
4 mm

 non shielded


Switch type

 N.C.
DC PNP

Signal Type
Connection

 Cable

Connection diagramm



Dimension (in mm)
Technical Specification
Operating voltage
Max. ripple
Voltage drop
Max. load current
No load current
Leakage current
Switching frequency
Switching hysteresis
Operating temperature
Temperature drift
Repeat accuracy
Switching state
Short-circuit proof
Overload protection
Reverse voltage protection
Protection category
EMC-level
Cable length
Utilisation category
Cable material

Q 15 x 8 x 32
10 - 30 V DC
 $\leq 10 \%$
1 V
100 mA
 ≤ 10 mA
 ≤ 10 μ A
250
 $\leq 15 \%$
-25 ° C to 70 ° C
 $\leq 10 \%$
 $\leq 3 \%$
LED
yes
yes
yes
IP67
DIN EN 60947-5-2: 2008
2 m
DC 13
PVC grau LIYY



KJ4-Q15KN32-DPÖ

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Cable cross

3x0.14 mm²

Errors and omissions exceptet