





Name
Order number
Switching distance
Mounting

Switch type


Signal Type
Connection

Connection diagramm

KJ2-M12MB70-VZS
08317251200
2 mm




shielded




N.O.

AC/DC



Cable



fine-pitch thread M12 x 70

Dimension (in mm)
Technical Specification
Operating voltage
Voltage drop
Max. load current
Leakage current
Switching frequency
Switching hysteresis
Operating temperature
Temperature drift
Repeat accuracy
Switching state
Short-circuit proof
Overload protection
Reverse voltage protection
Protection category
EMC-level
Material active face
Termination
Notes

20 - 250 V AC/DC

5 V

300 mA

≤ 1,7 mA

30

≤ 15 %

-25 ° C to 70 ° C

≤ 10 %

≤ 5 %

LED

yes

yes

yes

IP67

DIN EN 60947-5-2:2008

PCB

2m PVC 3x0,5mm²

Kurzschluss- und Überlastungsschutz rastend. Nach Beseitigung des Kurzschlusses muß die Spannungsversorgung für ca. 2s unterbrochen



KJ2-M12MB70-VZS

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

werden.

Errors and omissions exceptet