





Name
Order number
Matchcode
Switching distance
Mounting

KJ4-Q12KN-DPÖ-V1
08317613664
9861-3664
4 mm



non shielded


Switch type



N.C.

Signal Type
Connection
Connection diagramm

DC PNP
connector M8



Q 12 x 40 x 26

Dimension (in mm)
Technical Specification
Operating voltage
Max. ripple
Voltage drop
Max. load current
No load current
Leakage current
Switching frequency
Switching hysteresis
Operating temperature
Temperature drift
Repeat accuracy
Switching state
Short-circuit proof
Overload protection
Reverse voltage protection
Protection category
EMC-level
Housing material
Utilisation category
Termination

10 - 30 VDC
 $\leq 10 \%$
2,4 V
200 mA
 $\leq 13 \text{ mA}$
 $\leq 10 \mu\text{A}$
800
 $\leq 15 \%$
-25 ° C to 70 ° C
 $\leq 10 \%$
 $\leq 2 \%$
LED
yes
yes
yes
IP67
DIN EN 60947-5-2:2008
PBT
DC 13
Connector M8 3pin



KJ4-Q12KN-DPÖ-V1

Pulsotronic GmbH & Co. KG Neue Schichtstraße 14b 09366 Niederdorf Deutschland +49 (0)37296 930-200

Errors and omissions exceptet