



DC - 3 WIRE-SHORT BODY Brass, Nickel Plated (BN), Cylindrical, Threaded, 10-30V DC, 250mA, LED for Output Energized





- IEC (529) IP67 (NEMA 1, 3, 4, 6, 12, 13) Protection
- Short Circuit Protection
- Overload Protection
- Reverse Polarity Protection
- Wire Break Resistance
- Transient Voltage Protection
- Temperature Range: -25 to 70°C (-13 to 158°F)

M30 Flush Mount				M30 Non-Flush Mount	
Sensing Distance 10mm (.39 in.)				15mm (.59 in.)	
Cable or Connector Style Cat. No.		Cable		Cable	65
PNP	Normally Open		AIK30F10AP024-2M	AIK30F10AP024-Q65	
NPN	Normally Open		AIK30F10AN024-2M	AIK30F10AN024-Q65	
Ripple Voltage			≤10%		
Voltage Range			10-30V		
Supply Current			≤15 mA		
Max. Load Current			250 mA		
Voltage Drop Across Sensor			≤2.5V		
Max. Leakage Current			≤1 µA		
Switching Frequency			300 Hz		
Hysteresis			≤1.0mm		
Temperature Drift			≤±20µm/K		
Repeatability			≤0.5mm		

Fixed Cable
PVC 2m (6ft. 6in.). For other cable lengths and/or PUR cable, please consult Altech. Supplied with brass, nickel plated locknuts.



65 Style Connector
4-pin, Micro style, 12mm (.47 in.). Supplied with brass, nickel plated locknuts.



Note: Sensor dimensions in mm.

Metric/in. Conversion Table

1.5 mm = .06 in.	23.0 mm = .08 in.
2.0 mm = .08 in.	28.0 mm = 1.10 in.
4.0 mm = .16 in.	30.0 mm = 1.18 in.
5.0 mm = .20 in.	32.0 mm = 1.26 in.
6.0 mm = .23 in.	34.0 mm = 1.34 in.
8.0 mm = .31 in.	40.0 mm = 1.57 in.
10.0 mm = .39 in.	50.0 mm = 1.97 in.
12.0 mm = .47 in.	51.0 mm = 2.01 in.
15.0 mm = .59 in.	60.0 mm = 2.36 in.
18.0 mm = .70 in.	80.0 mm = 3.12 in.



This table converts millimeters to inches in reference to the illustrations included on these pages.

If you do not see a covered dimension, multiply mm by 0.03937 to convert to inches.

Wiring Diagrams

Note: Wire colors are applicable on cables purchased from Altech

PNP



NPN

