

T H E R M O M E T R I C S
A COMMITMENT TO EXCELLENCE

Type YM Series

Thermometrics PTC Thermistors



Thermometrics YM Series consists of a range of radially-wired PTC disc thermistors with silicone resin coating.

Features

- Fast switching times
- Operation up to 265V rms
- Wide range of operating current levels
- Excellent stability
- Fail-safe operation
- Solid state
- High performance barium titanate ceramic
- Suitable for automatic PCB insertion

Applications

- Designed for general purpose over-current, overvoltage and direct over-temperature protection

Packaging

All types in the YM range are available loose-packed, as shown in the drawing. Devices are also available on bandolier (tape & reel): types with diameter ≤ 12 mm comply with IEC 286-2.

To identify the packaging required, replace N in the product codes shown in table as follows:

YM

BandolieredR*
Loose-packedN

YQS

Bandoliered Add T suffix

Pack quantities:

Loose-packed500-2500/box
Bandoliered375-1500/reel


*YM120D260N150

*YM120D370N100

Not available taped and reeled

Amphenol

Advanced Sensors



Electrical Specifications

Maximum Operating Voltage

265V rms

Switch Temperature

120°C nominal

Tolerance on R_{25}

±20%

Ambient Temperature Range

At Storage: -25 to +155°C

At Maximum Voltage: 0 to +55°C

Lead Wire Material

Tin-coated copper

Body Coating

Silicone resin, green

Part Number	Replacement for	R @ 25°C Ω	Maximum Current without Tripping (I_m) mA		Minimum Trip Current (I_t) mA		Maximum Overload Current (I_{mo}) A	Maximum Residual Current (I_{res}) mA	D (max) mm	T (max) mm	H (max) mm
			T=25°C	T=55°C	T=25°C	T=10°C					
YM120C15N182		1800	16	14	23	28	0.1	5	4	5	8
YM120C20N122		1200	20	17	28	34	0.1	6	4	5	8
YQS8070	YM120C30N601	600	22	18	40	46	0.2	5	4.5	5	8
YQS8069	YM120C45N301	300	33	26	55	62	0.2	7	4.5	5	9
YQS8068	YM120C80N101	100	65	50	98	108	0.4	7	5.5	5	12
YQS8067	YM120D105N600	60	85	65	131	144	0.6	9	6	4.5	12
YM120D125N450		45	110	85	155	170	0.7	9	7	4.5	12
YQS8066	YM120D150N330	33	128	99	181	198	0.9	12	7.5	4.5	12
YM120D170N250		25	161	125	228	250	1.1	10	8.5	4.5	13
YQS8065	YM120D200N200	20	168	130	265	298	1.3	10	9.5	4.5	15
YM120D260N150		15	234	181	330	362	1.7	12	11.5	4.5	16
YM120D370N100		10	314	243	444	486	2.7	16	14.5	4.5	18

Amphenol
Advanced Sensors

© 2023 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.