SFH 3219

TOPLED® Lens

Silicon NPN Phototransistor

Applications

- Electronic Equipment
- White Goods

Features:

- Package: clear epoxy
- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)
- High linearity
- Same package as SFH 4249, SFH 4259
- Suitable for all soldering methods
- Spectral range of sensitivity: (typ) 450 ... 1150 nm

Ordering Information

Type	Photocurrent [1]	Photocurrent [2]	Ordering Code
		typ.	
	V_{CE} = 5 V; λ = 950 nm; E_e = 0.1 mW/cm²	V_{CE} = 5 V; λ = 950 nm; E_e = 0.1 mW/cm²	
	I_{PCE}	I_{PCE}	
SFH 3219-Z	≥ 71 µA	85 µA	Q65110A2651

Maximum Ratings

T_A = 25 °C

Parameter	Symbol		Values
Operating temperature	T_{op}	min. max.	-40 °C 100 °C
Storage temperature	T_{stg}	min. max.	-40 °C 100 °C
Collector-emitter voltage	V_{CE}	max.	35 V
Collector current	I_C	max.	15 mA
Collector surge current τ ≤ 10 µs	I_{CS}	max.	75 mA
Total power dissipation	P_{tot}	max.	165 mW
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)	V_{ESD}	max.	2 kV

Characteristics

T_A = 25 °C

Parameter	Symbol		Values
Wavelength of max sensitivity	$\lambda_{S\ max}$	typ.	990 nm
Spectral range of sensitivity	$\lambda_{10\%}$	typ.	450 ... 1150 nm
Dimensions of chip area	L x W	typ.	0.45 x 0.45 mm x mm
Radiant sensitive area	A	typ.	0.038 mm²
Half angle	φ	typ.	25 °
Dark current V_{CE} = 5 V	I_{CE0}	typ. max.	1 nA 50 nA
Rise time I_C = 1 mA; λ = 0 nm; V_{CC} = 5 V; R_L = 1 kΩ	t_r	typ.	7 µs
Fall time I_C = 1 mA; λ = 0 nm; V_{CC} = 5 V; R_L = 1 kΩ	t_f	typ.	7 µs
Collector-emitter saturation voltage [3)] I_C = 20 µA, E_e = 0.1 mW/cm²	V_{CEsat}	typ.	150 mV
Capacitance V_{CE} = 0 V; f = 1 MHz; E = 0	C_{CE}	typ.	5 pF
Thermal resistance junction ambient real	R_{thJA}	max.	450 K / W

Relative Spectral Sensitivity [4), 5)]

$S_{rel} = f(\lambda)$



Directional Characteristics [4), 5)]

$S_{rel} = f(\varphi)$



OSRAM
Opto Semiconductors

Photocurrent 4), 5)

$I_{PCE} = f(V_{CE})$; E_e = Parameter



Dark Current 4), 5)

$I_{CE0} = f(V_{CE})$; E = 0



Collector-Emitter Capacitance 4), 5)

$C_{CE} = f(V_{CE})$; f = 1 MHz; E = 0



OSRAM
Opto Semiconductors

Dark Current [4)]

$I_{CE0} = f(T_A)$; V_{CE} = 20 V; E = 0 ; E_e = 0 mW/cm²; 0



Photocurrent [4)]

$I_{PCE,rel} = f(T_A)$; V_{CE} = 5 V; E_v = 0 lx



Power Consumption

$P_{tot} = f(T_A)$



OSRAM
Opto Semiconductors

Dimensional Drawing [6)]



Further Information:

Approximate Weight: 37.0 mg

Package marking: Collector

Pin	Description
1	emitter
2	collector

Recommended Solder Pad [6)]



Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E



OSRAM
Opto Semiconductors

Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat*) 25 °C to 150 °C			2	3	K/s
Time t_S T_{Smin} to T_{Smax}	t_S	60	100	120	s
Ramp-up rate to peak*) T_{Smax} to T_P			2	3	K/s
Liquidus temperature	T_L		217		°C
Time above liquidus temperature	t_L		80	100	s
Peak temperature	T_P		245	250	°C
Time within 5 °C of the specified peak temperature T_P - 5 K	t_P	10	20	30	s
Ramp-down rate* T_P to 100 °C			3	4	K/s
Time 25 °C to T_P				480	s

All temperatures refer to the center of the package, measured on the top of the component
* slope calculation DT/Dt: Dt max. 5 s; fulfillment for the whole T-range

Taping [6)]



C63062-A3636-B4-03

Tape and Reel [7)]



Leader: min. 400mm*
Trailer: min. 160mm*
*)Dimensions acc. to IEC 60286-3; EIA 481-E

Reel Dimensions

A	W	N_{min}	W_1	$W_{2\,max}$	Pieces per PU
330 mm	12 + 0.3 / - 0.1 mm	60 mm	12.4 + 2 mm	18.4 mm	2000

Barcode-Product-Label (BPL)



OHA04563

Dry Packing Process and Materials [6)]



OHA00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.

Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **exempt group (exposure time 10000 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

For further application related information please visit www.osram-os.com/appnotes

Disclaimer

Attention please!
The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact our Sales Organization.
If printed or downloaded, please find the latest version on the OSRAM OS website.

Packing
Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications
OSRAM OS components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.
OSRAM OS products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using OSRAM OS components in product safety devices/applications or medical devices/applications, buyer and/or customer has to inform the local sales partner of OSRAM OS immediately and OSRAM OS and buyer and /or customer will analyze and coordinate the customer-specific request between OSRAM OS and buyer and/or customer.

Glossary

1) **Photocurrent:** The photocurrent values are measured (by irradiating the devices with a homogenous light source and applying a voltage to the device) with a tolerance of ±11 %.

2) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ±0.1 and dimensions are specified in mm.

3) **IPCEmin:** IPCEmin is the min. photocurrent of the specified group.

4) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.

5) **Testing temperature:** TA = 25°C (unless otherwise specified)

6) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ±0.1 and dimensions are specified in mm.

7) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

Revision History

Version	Date	Change
1.5	2021-07-14	Schematic Transportation Box Dimensions of Transportation Box

Published by OSRAM Opto Semiconductors GmbH
Leibnizstraße 4, D-93055 Regensburg
www.osram-os.com © All Rights Reserved.

EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，不含有毒有害物质或元素。

OSRAM
Opto Semiconductors