

## Daker DK 4.5kVA Online UPS, 1x outlet termination block

A-17063 4016032343981



### Daker DK 4.5kVA Online UPS, 1x outlet termination block

**Online UPS 1kVA, 6x IEC C13 outputs, SNMP-Slot, LCD Display, Hot Swap Battery 440x680x176 mm (WxDxH)**

The Daker On-Line UPS enclosures in Combirack are useable as tower or rackmountable. With the display you can control all system-relevant functions and check the status of the UPS enclosure, e.g. workload, remaining bridging time and system issues. With IEC outlets, USB, RS232, SNMP-Slot and a LCD-Display the USP enclosures are the best solution for professional usage. The models A-17060 and A-17061 can be endowed with additional Battery-Racks for increasement of bridging time. An additional battery loading enclosure is integrable in every battery rack to ensure a safer and faster loading of the battery system.



- 1 Weight: 52 kg
- 1 1x input terminal block, 1x output terminal block
- 1 Safeguards: Overload, bypass, interrupt of working by termination of autonomic time and overheating
- 1 Operating temperature range: 0 up to +40 °C
- 1 Operating moisture range: 20 up to 80 % non-condensation
- 1 Safety class according IEC 529: IP21
- 1 Noise level in 1 m distance: < 50 dBA
- 1 Nominal input voltage: 230V
- 1 Nominal output voltage: 230V ± 2%
- 1 Range of nominal input voltage: 160V up to 280V
- 1 Nominal input frequency: 50 or 60 Hz ± 5Hz
- 1 Maximum input volt power: 25 Arms
- 1 Number of input phases: Monophase
- 1 Number of output phases: Monophase
- 1 Battery operation: Sine-shaped
- 1 Operating type: On line - double converter
- 1 Active output power with nominal load: 4050W
- 1 Apparent output power with nominal load: 4.5kVA
- 1 Overload capacity: 105% non-stop operation, 120% for 30 seconds, 140% for 10 seconds
- 1 Battery operating autonomy: 6 minutes
- 1 Battery charging time: 4 hours on 90% of loading
- 1 20 maintenance-free, leaded and sealed batteries, 12V 5Ah
- 1 Electromagnetic compatibility, Immunitay - Emissiones: According to EN 62040-2
- 1 Safeguards: According to EN 62040-1
- 1 Characteristic power: According to EN 62040-3
- 1 Dimensions (HxWxD): 176,440,680 mm

## Daker DK 4.5kVA Online UPS, 1x outlet termination block

A-17063 4016032343981

### → Logistics

|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³         |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-------------|
| Packaging Unit Carton        | 1               | 0,00           | 0,00          | 0,00          | 0,00           | 0,00        |
| Packaging Unit Inside        | 1               | 0,00           | 0,00          | 0,00          | 0,00           | 0,00        |
| Packaging Unit Single        | 1               | 0,00           | 680,00        | 440,00        | 176,00         | 52659200,00 |
| Net single without Packaging | 1               | 0,00           | 0,00          | 0,00          | 0,00           | 0,00        |