

Daker DK 6kVA Online UPS, 1x outlet termination block

A-17064 4016032343998



Daker DK 6kVA Online UPS, 1x outlet termination block Online UPS 1kVA, 6x IEC C13 outputs, SNMP-Slot, LCD Display, Hot Swap Battery 440x680x176 mm (WxDxH)

The Daker On-Line UPS enclosures in Combirack are useable as tower or rackmountable. With the display you can control all system-relevant functions and check the status of the UPS enclosure, e.g. workload, remaining bridging time and system issues. With IEC outlets, USB, RS232, SNMP-Slot and a LCD-Display the USP enclosures are the best solution for professional usage. The models A-17060 and A-17061 can be endowed with additional Battery-Racks for increasement of bridging time. An additional battery loading enclosure is integrable in every battery rack to ensure a safer and faster loading of the battery system.



- 1 Weight: 52 kg
- 1 1x input terminal block, 1x output terminal block
- 1 Safeguards: Overload, bypass, interrupt of working by termination of autonomic time and overheating
- 1 Operating temperature range: 0 up to +40 °C
- 1 Operating moisture range: 20 up to 80 % non-condensation
- 1 Safety class according IEC 529: IP21
- 1 Noise level in 1 m distance: < 50 dBA
- 1 Nominal input voltage: 230V
- 1 Nominal output voltage: 230V ± 2%
- 1 Range of nominal input voltage: 160V up to 280V
- 1 Nominal input frequency: 50 or 60 Hz ± 5Hz
- 1 Maximum input volt power: 33 Arms
- 1 Number of input phases: Monophase
- 1 Number of output phases: Monophase
- 1 Battery operation: Sine-shaped
- 1 Operating type: On line - double converter
- 1 Active output power with nominal load: 5,4kW
- 1 Apparent output power with nominal load: 6kVA
- 1 Overload capacity: 105% non-stop operation, 120% for 30 seconds, 140% for 10 seconds
- 1 Battery operating autonomy: 4 minutes
- 1 Battery charging time: 4 hours on 90% of loading
- 1 20 maintenance-free, leaded and sealed batteries, 12V 5Ah
- 1 Electromagnetic compatibility, Immunity - Emissions: According to EN 62040-2
- 1 Safeguards: According to EN 62040-1
- 1 Characteristic power: According to EN 62040-3
- 1 Dimensions (HxDxW): 176,440,680 mm

Daker DK 6kVA Online UPS, 1x outlet termination block

A-17064 4016032343998

→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0,00	0,00	0,00	0,00	0,00
Packaging Unit Inside	1	0,00	0,00	0,00	0,00	0,00
Packaging Unit Single	1	0,00	680,00	440,00	176,00	52659200,00
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00