

## Line-Interactive UPS, 600 VA/360 W

DN-170013-1 4016032345077



### **DIGITUS Line-Interactive UPS, 600VA/360W** **12V/7Ah X1 battery, 2x Schuko, AVR, WRJ-11, LED display**

The DIGITUS® Line-Interactive UPS come with a compact size and an excellent microprocessor control, which guarantees high reliability. With an user friendly operation they provide high performance protection for your business and office computer systems against data loss and damage. Features like overload-, discharge and overcharge protection, cold start functions and energy saving features, as well as an acoustic alarm system are just a few advantages of the DIGITUS® Line-Interactive UPS units.

- 1 Capacity: 600 VA/360 W
- 1 Input voltage: 230 VAC
- 1 Voltage range: 162-290 VAC
- 1 Frequency range: 50 Hz (auto sensing)
- 1 Output voltage: 230 VAC ± 10%
- 1 AC voltage regulation (battery mode): 10%
- 1 Frequency range (battery mode): 50 Hz ± 1%
- 1 Typical transfer time: 2-6 ms
- 1 Waveform (battery mode): Simulated sine wave
- 1 Battery: 12V/7Ah x 1
- 1 Typical recharge time: 4 hours to recover 90% of capacity
- 1 With overload-, discharge-, and overcharge protection
- 1 Boost and buck AVR for voltage stabilization
- 1 Auto restart while AC is recovering
- 1 Alarm sounds: Battery mode (sounding every 10 sec.), low battery (sounding every second), overload (sounding every 0.5 seconds), fault (continuously sounding)
- 1 Dimensions (HxWxD): 279x101x142 mm
- 1 Net weight: 4.2 kg
- 1 Humidity: 0-90% RH @ 0 °C to +40 °C (non condensing)
- 1 Noise level: Less than 40 dB

## Line-Interactive UPS, 600 VA/360 W

DN-170013-1 4016032345077

### → Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0,00	0,00	0,00	0,00	0,00
Packaging Unit Inside	1	0,00	0,00	0,00	0,00	0,00
Packaging Unit Single	1	0,00	0,00	0,00	0,00	0,00
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00