

Industrial power supply 24V/25W

DN-653025 4016032344506



Power Supply 24V/25W for Industrial Switch
Input range: 90-264VAC or 127-380VDC, 47-63Hz UL, be

Standard / Din Rail mounting dual purpose

The DN-653025 industrial power supply is the perfect solution for lower power requirements. Its no-load consumption is lower than 0.3W, furthermore it is compliant with high efficiency power criterions (80Plus) and 2010 ErP (Energy Conservation Regulation), as well as important safety standards. The case and -15 ~ 50°C operating temperature are adjusted for extreme industrial environments, where in addition the convection cooling provides high reliability.

- 1 Input voltage range: 90 ~ 264VAC, 127 ~ 380VDC
- 1 Input Frequency range: 47 ~ 63Hz
- 1 AC inrush current: Cold start, 20A/ 110VAC, 40A/ 220VAC
- 1 Hold-up time: Rated load, 13ms / 220VAC
- 1 Short protection: Autorecovery
- 1 Overload protection: Automatic power limited
- 1 Operating Temperature: -15 ~ 50°C, Ambient
- 1 Ripple & Noise: 240mV
- 1 Standard / Din Rail mounting dual purpose
- 1 No-load consumption is lower than 0.3W
- 1 Comply with high efficiency power 80plus criterion
- 1 2010 ErP (Energy Conservation Regulation) compliant
- 1 Convection cooled high reliability
- 1 Output modify range: 3V ~ 200VDC



Industrial power supply 24V/25W

DN-653025 4016032344506



→ Logistics	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0,15	6,00	10,50	4,50	283,50
Packaging Unit Inside	1	0,15	6,00	10,50	4,50	283,50
Packaging Unit Single	1	0,15	6,00	10,50	4,50	283,50
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00

Country of origin: China

