

Industrial power supply 48V/300W

DN-653300 4016032344537



Power Supply 48V/300W for Industrial Switch
Input range: 90-132/180-264VAC (selectable) or 220-380VDC, 47-63Hz

Standard / Din Rail mounting dual purpose

The DN-653300 industrial power supply is the perfect solution for higher power requirements. Its no-load consumption is lower than 0.5W, furthermore it is compliant with high efficiency power criterions (80Plus) and 2010 ErP (Energy Conservation Regulation), as well as important safety standards. The compact size, solid case and -15 ~ 50°C operating temperature are adjusted for extreme industrial environments, where in addition the convection cooling provides high reliability. The DN-653300 is also equipped with a "Output Voltage Monitor" display.



- 1 Input voltage range: 90 ~ 132VAC / 180 ~ 264VAC(Selectable), 200 ~ 380VDC
- 1 Input Frequency range: 47 ~ 63Hz
- 1 AC inrush current: Cold start, 20A/ 110VAC, 40A/ 220VAC
- 1 Hold-up time: Rated load, 13ms / 220VAC
- 1 Short protection: Autorecovery
- 1 Overload protection: Automatic power limited
- 1 Operating Temperature: -15 ~ 50°C, Ambient
- 1 Ripple & Noise: 480mV
- 1 Standard / Din Rail mounting dual purpose
- 1 Compact size
- 1 Comply with high efficiency power 80plus criterion
- 1 "Output Voltage Monitor" display
- 1 Convection cooled high reliability
- 1 Output modify range: 3V ~ 200VDC

Industrial power supply 48V/300W

DN-653300 4016032344537



→ Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	15	12,00	44,00	35,00	25,00	38500,00
Packaging Unit Inside	1	0,80	6,50	14,00	12,50	1137,50
Packaging Unit Single	1	0,80	6,50	14,00	12,50	1137,50
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00

Country of origin: China

