DIGITUS IPv6 Gigabit Ethernet PoE Web Smart 24 port Switch, 2 Combo ports

4016032307297 DN-95316



DIGITUS Web Smart Gigabit Ethernet PoE+ Switch 24-port RJ45, 2-port SFP, Half Powered, IPv6 Rack Mount, 195W

Integrated Power over Ethernet (PoE) and network management features for small and medium network environments

With Power over Ethernet (IEEE802.3af/at) technology the power is used more efficiently due to the maximum power will only be requested when it is needed. Thus providing cost savings by reducing the need for additional power cables and outlets.

- 1 Gigabit Ethernet Web Smart IPv6 PoE+ Switch
- IPv6 and IPv4 Dual Protocol Future Proof
- 1 24 RJ45 ports
- 2 shared SFP ports
- PoE Power Output 48V/DC, max. 30W per Port
- PoE On/Off setting via Web Management
- Maximum Power Consumption of 195 Watt: Distribution according to the demand. For example 6 Ports with Full Power of 30 Watt or 24 Ports with half power of 7 Watt according to Class 2 for VoIP appliances
- 9 KB Jumbo Frames
- Store and Forward technology
- Compatible to the following standards: IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.1Q, 802.3x, 802.1x, 802.3ad, 802.1d, 802.1p, 802.3p, 802.3af and 802.3at
- 1 Auto MDI / MDI-X function
- 16K MAC addresses
- 8 QoS classes
- Port Mirroring for efficient network surveillance
- Port Trunk for Bandwidth Aggregation
- VLAN for Performance and Security
- 802.1x Port Authentication
- SNMP v1 and v2c Network Management
- 1 Built-in Web-based management
- Suitable for rack mount (incl. mounting bracket)
- Operating system independent, supports e.g. Windows, Mac OS, Linux and Sun

Package Content

- 1 Switch
- Power Cable
- Quick installation guide
- 1 Product support CD-ROM
- 1 483mm (19") Mounting Accessories

www.assmann.com



DIGITUS IPv6 Gigabit Ethernet PoE Web Smart 24 port Switch, 2 Combo ports

DN-95316 4016032307297

→ Logistics	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	2	8,50	53,00	34,00	21,00	37842,00
Packaging Unit Inside	1	4,25	9,10	30,60	50,00	13923,00
Packaging Unit Single	1	4,25	9,10	30,60	50,00	13923,00
Net single without Packaging	1	0,00	44,00	22,00	4,40	4259,20

→ Operating systems





→ Packaging type



Country of origin: Taiwan



www.assmann.com