

MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES


The MCA-10 series offers 10W ultraminiature modular switching power supplies, designed for high performance and reliability. Available in single, dual, and triple outputs, they feature a universal 90 to 264VAC input and output voltages from 3.3VDC to 24VDC. With 3,000 input-to-output isolation, they ensure safety and protection. these power supplies are available in PCB and chassis mount packages, offering versatile installation options to accommodate different design and space constraints. Whether for industrial, commercial, or consumer electronics, the MCA-10 series provides a reliable and efficient power solution.

c **UL** [®] **US** CB



HOW TO ORDER

MSCC-0100/DRL



FEATURES

INPUT VOLTAGE

90-264 VAC (100-240 VAC, nom.)

INPUT FREQUENCY

47-440Hz, 50-60Hz nom.

OPERATING TEMPERATURE

0 to +50°C(FL) See Derate* (Free-air Convection)

SAFETY APPROVALS

ESD: EN61000-4-2, 6kV Contact, 8kV Air
 RS: EN61000-4-3
 EFT: EN61000-4-4, 2kV on AC Line
 Surge: EN61000-4-5, 1kV L-N
 CS: EN61000-4-6, 3V EMF
 Dips (Note 8): EN61000-4-11

INPUT-OUTPUT ISOLATION


3000VAC, 60S

OPERATING FREQUENCY

140 kHz, typ., fixed

EFFICIENCY

See the model selection chart




MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES

PARAMETERS

MCA10

Input Voltage	90-264VAC (100-240VAC, nom.)
Input Frequency	47-440Hz, 50-60Hz Nom.
Input Current (LL/HL)	0.3A/0.5A
Inrush Current (Note 1)	20A@100VAC, 40A@200VAC, typ
Leakage Current	<3.5mA at 264Vin, 50Hz
Output Voltage/Current	See Model Selection Chart
Preset Accuracy	Single & Matched Dual: $\pm 1\%$ nom.
Unmatched	Dual- 0108 (5V, 12V): $\pm 2\%$, $\pm 5\%$ nom. Triple O/P (5, $\pm O/P$): $\pm 1\%$, $\pm 5\%$ nom.
Voltage Adjust	$\pm 6\%$, typ
Load/Line Regulation (Note 3)	See Model Selection Chart
Cross Regulation (Note 11)	Dual O/P: 3% max.
Unmatched	Dual -0108 (5V, 12V): $\pm 1\%$, $\pm 5\%$ max. Triple O/P: N/A, $\pm 0.5\%$ max.
Temperature Coefficient	$\pm 0.03\%/^{\circ}\text{C}$
Ripple/Noise (Note 2)	See Model Selection Chart
Over Voltage Protection	Clamp*
Start Up	<4S
Hold Up Time	20mS, typ
Rise Time	<20mS
Over-Shoot/Under-Shoot	<10% nominal O/P voltage
Short Circuit Protection	Continuous, self-recovering*
* These are stress ratings. Exposure of the devices to any of these conditions may adversely affect long-term reliability. Proper operation under conditions other than the standard operating conditions is neither warranted nor implied.	
On/Off Control (Note 4)	Open Collector Logic "1"/Open=ON
Input-Output Isolation	Logic "0"/GND=OFF
Insulation Resistance (Note 6)	$\geq 20\text{M}\Omega$
Operating Frequency	140 KHz, typ., fixed
Efficiency	See Model Selection Chart
Safety UL/cUL:	UL60950-1 2 nd ed. C22.2 60950-1 2 nd ed.
CB:	IEC60950-1 2 nd ed.



MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES

PARAMETERS


MCA10

Oper. Temperature	0 to +50°C FL See Derate* (Free-air Convection)
Relative Humidity (Note 5)	0-95%, Non-Condensing
Storage Temperature	-25 to +71°C *
MTBF, Single/Multi O/P (Note 9)	180,000 / 110,000 Hrs
Vibration (Note 10)	2G Peak, 10~500Hz, 3 Axes
Drop Test	70 cm
EMS:	ESD: EN61000-4-2, 6kV Contact, 8kV Air RS: EN61000-4-3 EFT: EN61000-4-4, 2kV on AC Line Surge: EN61000-4-5, 1kV L-N CS: EN61000-4-6, 3V EMF Dips (Note 8): EN61000-4-11
EMI	CISPR EN55011 class B
Case Material	Rynite, 94V-0 Rated
Construction	Encapsulated, Soft Pot
Weight PCS/CHA	4.6 oz (130g) / 8.5 oz (241g)

NOTES

1. Cold Start and 25°C
2. Test by DC loading side parallel with a 0.1uF ceramic capacitor and measured bandwidth with DC-20MHz.
3. Regulation includes line, cross temperature drift, and tolerance variation Load regulation measured from 20% to Full load. All other outputs at nominal load.
4. No termination is necessary with the Control pin to maintain constant "On" operation.
5. Operating or Storage
6. 500Vdc, 1 Sec between primary to secondary
7. FR: 80MHz-2.5GHz; Field Strength 3V/M
8. 95% 250Cy, 70% 25Cy, 40% 5Cy, 5% 0.5Cy
9. MIL STD 217, 25°C
10. Tested with a shipping container for 30 minutes
11. Measured at nominal load with the other output(s) varied between 20% and 100% nominal load.

* These are stress ratings. Exposure of the devices to any of these conditions may adversely affect long-term reliability. Proper operation under conditions other than standard operating conditions is neither warranted nor implied.




MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES

MODEL NUMBER OUTPUT VOLTAGE OUTPUT AMPS OUTPUT WATTS RIPPLE & NOISE MAX. (NOTE 2) LINE/LOAD REG. MAX. (NOTE 3) EFFICIENCY

SINGLE OUTPUT – PCB Mount						
MSCA-0100	3.3VDC	2.5	8W	100mV pk-pk	1% / 1%	62% nom.
MSCA-0101	5VDC	2.0	10W	100mV pk-pk	1% / 1%	72% nom.
MSCA-0104	9VDC	1.1	10W	75mV pk-pk	1% / 1%	72% nom.
MSCA-0102	12VDC	0.85	10W	75mV pk-pk	0.5% / 0.5%	75% nom.
MSCA-0103	15VDC	0.67	10W	75mV pk-pk	0.5% / 0.5%	76% nom.
MSCA-0105	24VDC	0.42	10W	75mV pk-pk	0.5% / 0.5%	78% nom.
SINGLE OUTPUT – Chassis Mount						
MSCC-0100	3.3VDC	2.5	8W	100mV pk-pk	1% / 1%	62% nom.
MSCC-0101	5VDC	2.0	10W	100mV pk-pk	1% / 1%	72% nom.
MSCC-0104	9VDC	1.1	10W	75mV pk-pk	1% / 1%	72% nom.
MSCC-0102	12VDC	0.85	10W	75mV pk-pk	0.5% / 0.5%	75% nom.
MSCC-0103	15VDC	0.67	10W	75mV pk-pk	0.5% / 0.5%	76% nom.
MSCC-0105	24VDC	0.42	10W	75mV pk-pk	0.5% / 0.5%	78% nom.
SINGLE OUTPUT – DIN Rail Mount						
MSCC-0100/DRL	3.3VDC	2.5	8W	100mV pk-pk	1% / 1%	62% nom.
MSCC-0101/DRL	5VDC	2.0	10W	100mV pk-pk	1% / 1%	72% nom.
MSCC-0104/DRL	9VDC	1.1	10W	75mV pk-pk	1% / 1%	72% nom.
MSCC-0102/DRL	12VDC	0.85	10W	75mV pk-pk	0.5% / 0.5%	75% nom.
MSCC-0103/DRL	15VDC	0.67	10W	75mV pk-pk	0.5% / 0.5%	76% nom.
MSCC-0105/DRL	24VDC	0.42	10W	75mV pk-pk	0.5% / 0.5%	78% nom.
DUAL OUTPUT – PCB Mount						
MDCA-0106	±12VDC	±0.42	10W	75mV pk-pk	1% / 3%	75% nom.
MDCA-0107	±15VDC	±0.34	10W	75mV pk-pk	1% / 3%	72% nom.
MDCA-0108	+5/12 VDC	1/0.42	10W	100/150mV pk-pk	1% / 1%,5%	75% nom.
DUAL OUTPUT – Chassis Mount						
MSCC-0106	±12VDC	±0.42	10W	75mV pk-pk	1% / 3%	75% nom.
MSCC-0107	±15VDC	±0.34	10W	75mV pk-pk	1% / 3%	72% nom.
MSCC-0108	+5/12VDC	1/0.42	10W	100/150mV pk-pk	1% / 1%,5%	75% nom.
DUAL OUTPUT – DIN Rail Mount						
MSCC-0106/DRL	±12VDC	±0.42	10W	75mV pk-pk	1% / 3%	75% nom.
MSCC-0107/DRL	±15VDC	±0.34	10W	75mV pk-pk	1% / 3%	72% nom.
MSCC-0108/DRL	+5/12VDC	1/0.42	10W	100/150mV pk-pk	1% / 1%,5%	75% nom.




MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES

MODEL NUMBER	OUTPUT VOLTAGE	OUTPUT AMPS	OUTPUT WATTS	RIPPLE & NOISE MAX. (NOTE 2)	LINE/LOAD REG. MAX. (NOTE 3)	EFFICIENCY
TRIPLE OUTPUT - PCB Mount						
MTCA-0109	+5,±12 VDC	1.5,0.1/0.1	10W	75, ±100mV pk-pk	0.6%, ±0.2 / 0.5%	70% nom.
MTCA-0111	+5,±15 VDC	1.4,0.1/0.1	10W	75, ±100mV pk-pk	0.6%, ±0.2 / 0.5%	70% nom.
TRIPLE OUTPUT - Chassis Mount						
MTCC-0109	+5,±12 VDC	1.5,0.1/0.1	10W	75, ±100mV pk-pk	0.6%, ±0.2 / 0.5%	70% nom.
MTCC-0111	+5,±15 VDC	1.4,0.1/0.1	10W	75, ±100mV pk-pk	0.6%, ±0.2 / 0.5%	70% nom.
TRIPLE OUTPUT- DIN Rail Mount						
MTCC-0109/DRL	+5,±12 VDC	1.5,0.1/0.1	10W	75, ±100mV pk-pk	0.6%, ±0.2 / 0.5%	70% nom.
MTCC-0111/DRL	+5,±15 VDC	1.4,0.1/0.1	10W	75, ±100mV pk-pk	0.6%, ±0.2 / 0.5%	70% nom.


*These Specifications are subject to change at any time without prior notification.
All Specifications are typical at nominal input, full load, and 25°C unless otherwise noted.*




MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES

MECHANICAL DIMENSION- CHASSIS MOUNT




PIN-OUT VIEWED FROM BOTTOM



Model	Single	Dual	Unmatched Dual	Triple
Type/Pin#				
1	AC HI	AC HI	AC HI	AC HI
2	AC LO	AC LO	AC LO	AC LO
3	GND	GND	GND	GND
4	No Pin	No Pin	No Pin	+Vout
5	No Pin	No Pin	No Pin	Out Com
6	+Vout	+Vout	+12Vout	No Pin
7	No Pin	No Pin	No Pin	-Vout
8	No Pin	Out Com	+5Vout	+5Vout
9	-Vout	-Vout	Out Com	5V Ret
10	Ctrl	Ctrl	Ctrl	Ctrl

Tolerance : .XX ± 0.02 [0.508]
.XXX ± 0.01 [0.254]


Dimensions shown in inch [mm]




MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES

MECHANICAL DIMENSION- CHASSIS MOUNT




Model Type / Pin#	Single	Match Dual	Unmatch Dual	Triple
1	AC LO	AC LO	AC LO	AC LO
2	GND	GND	GND	GND
3	AC III	AC III	AC III	AC III
4	Ctrl	Ctrl	Ctrl	Ctrl
5	-Vout	-Vout	Com	+5 Ret
6	-Vout	Com	Com	+5Vout
7	+Vout	Com	+5Vout	-Vout
8	+Vout	+Vout	+12Vout	+/- Com
9	N/C	N/C	N/C	+Vout



MCA10

10W ULTRAMINIATURE MODULAR SWITCHING POWER SUPPLIES

MECHANICAL DIMENSION- DIN RAIL



DIN Rail mounting kit available for Chassis-mount modules specifies part # M-DRL-01. Kit includes mounting plate, DIN Rail clip, and assembly hardware.

DERATE CURVE

