

■ Features

- Single output from 24W
- 100-240Vac Universal input
- Certificates: UL, cUL, CE
- OCP, OVP, OTP, and SCP
- Efficiency Level VI
- NEMA 5 Type 2 Wire A/C Cord & Plug
- Waterproof DC harness with washer
- IP68
- MTBF: 50,000 hours
- 2-year warranty
- Dimension: 102x49x33mm



*Product images are for illustrative purposes only and may vary from actual design.

■ Application

- Dry, Damp and Wet locations
- Industrial equipment

■ Model List

Custom Designs Available!

Model	Output Voltage	Output Current	Power	Certificates
DT024R-050-N52-WA-XX	5V	4.8A	24W	UL/cUL, CE
DT024R-120-N52-WA-XX	12V	2A	24W	UL/cUL, CE
DT024R-240-N52-WA-XX	24V	1A	24W	UL/cUL, CE

*Available in 0.1V increments please contact Autec Sales for more information

■ Technical Data

Input Voltage	100-240Vac
Line Frequency	50-60Hz
Input Current	600mA
Inrush Current	40A
Rated Output Voltage	5V-24V
Rated Output Current	1000mA-4800mA
Rated Power	18W
Output Ripple and Noise	200mVp-p
Turn On Delay Time	3S Max.
Rise time	40mS
Hold up time	5mS
Efficiency	85%min.
Over Voltage Protection	V out *120-150% Max.
Short Circuit Protection	Shut down
Over Current Protection	I out *120-150% Max.
Over Temperature Protection	Latch Protection

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com
 31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

April 18, 2019

■ Technical Data(cont.)

Leakage Current	0.25mA
Line Regulation	±1%
Load Regulation	±5%
Operating Temperature	-0 to 40°C
Storage Temperature	-10 to 80°C
Operating Relative Humidity	5 to 90% RH
Storage Relative Humidity	5 to 95% RH
Case Dimensions	102x49x33mm
Weight	TBA
Vibration Test Requirement	Operating: IEC 721-3-3 3M3
Transportation	IEC 721-3-2 2M2, 5-9Hz, A=3.5mm; 9-200Hz, Acceleration=5m/S ² ; 200-500Hz Acceleration=15m/S ² ; Axes., 10 cycles per axis


Note: When Over Current Protection is activated, the power supply will shutdown automatically. Once the abnormal condition resulting in the failure has been removed, the power supply will restart. When Over Voltage Protection or Over Temperature Protection is activated, the power supply will latch.

■ Safety & EMI Standards

Safety Standard	UL1310, UL8750
Insulation Resistance	Primary to secondary:5MΩ min at 500V DC.
Dielectric Strength Hi-Pot:	Primary to secondary:2000Vac5mA/3S for type test.
EMI Standard	Fcc Part 15; EN55015


■ Waterproof DC Harness with Washer Mechanical Diagram

- DT024R-XXX-N52-WA-2




■ Mechanical Diagram


- DT024R-XXX-N52-WA-XX



■ Output Current vs. Temperature

Temperature	40°C	45°C	50°C	55 °C	60°C	65°C	70°C
Output Current	2A	1.9A	1.8A	1.7A	1.6A	1.4A	1.2A





***Some Safety Agency Approvals may differ from what is shown. Contact Autec Sales!**

***Product images are for illustrative purposes only and may vary from actual design.**

***Specifications are subject to change without notice. Autec is not responsible for issues arising from errors or omissions.**