

■ Features

- Single output from 25-36W
- 100-240Vac Universal input
- Certificates: UL, cUL, CE
- SCP, OCP, OTP, and OVP
- Efficiency Level VI
- MTBF: 300,000 hours
- Dimension C14: 100x50x33mm
- 1 year Warranty



*Product images are for illustrative purposes only and may vary from actual design.

■ Application

- Consumer electronics and office equipment
- Industrial equipment

Custom Designs Available!

■ Model List

Model	Output Voltage	Output Current	Power	Certificates
DT036A-050-X-XX*	5V	5A	25W	UL, cUL, CE
DT036A-075-X-XX	7.5V	4A	30W	UL, cUL, CE
DT036A-085-X-XX	8.5V	3.52A	30W	UL, cUL, CE
DT036A-090-X-XX	9V	3.34A	30W	UL, cUL, CE
DT036A-120-X-XX	12V	3A	36W	UL, cUL, CE
DT036A-121-X-XX	12V	2.5A	30W	UL, cUL, CE
DT036A-135-X-XX	13.5V	2.66A	36W	UL, cUL, CE
DT036A-150-X-XX	15V	2.4A	36W	UL, cUL, CE
DT036A-160-X-XX	16V	2.25A	36W	UL, cUL, CE
DT036A-180-X-XX	18V	2A	36W	UL, cUL, CE
DT036A-240-X-XX	24V	1.5A	36W	UL, cUL, CE
DT036A-480-X-XX	48V	0.75A	36W	UL, cUL, CE

*Add -MX for 6-Pin Power Type Molex Output connector

■ Technical Data

Input Voltage	100-240Vac
Line Frequency	50-60Hz
Input Current	1A
Input Protection	Internal Primary Current Fuse
Configuration	IEC60320/C8, C14
Load Regulation	±5% (Typical)
Ripple	2% Vp-p Max. for Output Voltage @Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @Full Load
Ferrite Core	Optional

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com
 31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

April 19, 2019

■ Technical Data(cont.)


Over Voltage Protection	V out *120-150% Max.
Short Circuit Protection	Shut down
Over Current Protection	I out *120-150% Max.
Over Temperature Protection	Latch Protection
Dielectric Withstand	3,000Vac Primary-Secondary
Topology	Switching Flyback
Leakage Current	0.25mA
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332
Operating Temperature	0 to +40°C
Storage Temperature	-20 to +80°C
Operating Relative Humidity	20 to 80% RH
Storage Relative Humidity	10 to 90% RH
Cooling	Natural Convection Cooling
Case Dimensions	100x50x33mm(typ.) 4.0x2.0x1.3in
Weight	160g
Molex Plug	6-Pin Housing Molex 39-01-2060 Connector or similar
Material Flammability	UL94V-0

Note: When Over Current Protection is activated, the power supply will shutdown automatically. Once the abnormal condition resulting in the failure being removed, the power supply will restart. When Over Voltage Protection or Over Temperature Protection is activated, the power supply will latch.


■ Safety Approvals

Safety Standard	IEC62368-1
EMI Conduction & Radiation	Compliance to IEC55032 Class B
Harmonic Current	Compliance to EN61000-3-2-,3
EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11

■ DC Output Cable Mechanical Diagram



*Molex 39-01-2060 Connector or similar for models with an output current of 5A and above.





Output Cable Plug Pin Assignment

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

April 19, 2019



***Some Safety Agency Approvals may differ from what is shown. Contact Autec Sales!**

***Product images are for illustrative purposes only and may vary from actual design.**

***Specifications are subject to change without notice. Autec is not responsible for issues arising from errors or omissions.**

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

April 19, 2019