



■ Features

- Single output from 40-72W
- 100-240Vac Universal input
- Certificates: UL, cUL, CE
- No load power consumption < 0.21W
- OCP, OVP, OTP, and SCP
- Efficiency Level VI
- MTBF: 50,000 hours
- 2-year warranty



*Product images are for illustrative purposes only and may vary from actual design.

■ Application

- Consumer electronics and office equipment
- Industrial equipment

■ Model List

Custom Designs Available!

Model	Output Voltage	Output Current	Power	Certificates
DT070B-050-X-XX	5V	8A	40W	UL/cUL, CE
DT070B-070-X-XX	7V	5.7A	40W	UL/cUL, CE
DT070B-090-X-XX	9V	6A	54W	UL/cUL, CE
DT070B-120-X-XX	12V	5A	60W	UL/cUL, CE
DT070B-150-X-XX	15V	4A	60W	UL/cUL, CE
DT070B-190-X-XX	19V	3.4A	65W	UL/cUL, CE
DT070B-240-X-XX	24V	3A	72W	UL/cUL, CE
DT070B-280-X-XX	28V	2.6A	72W	UL/cUL, CE
DT070B-360-X-XX	36V	2A	72W	UL/cUL, CE
DT070B-480-X-XX	48V	1.5A	72W	UL/cUL, CE
DT070B-560-X-XX	56V	1.3A	72W	UL/cUL, CE

*Available in 0.1V increments please contact Autec Sales for more information


■ Protections

Over Voltage Protection	V out *120-150% Max.
Short Circuit Protection	Shut down
Over Current Protection	I out *120-150% Max.
Over Temperature Protection	Latch Protection

Note: When Over Current Protection is activated, the power supply will shut down automatically. Once the abnormal condition resulting in the failure being removed, the power supply will restart. When Over Voltage Protection or Over Temperature Protection is activated, the power supply will latch.

■ Mechanical Diagram

*Available A/C inlet with C6, C14



***Some Safety Agency Approvals may differ from what is shown. Contact Autec Sales!**

***Product images are for illustrative purposes only and may vary from actual design.**

***Specifications are subject to change without notice. Autec is not responsible for issues arising from errors or omissions.**

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

April 22, 2019