

■ Features

- Single output from 192-200W
- 100-240Vac Universal input
- IEC62368-1 approval
- Gallium Arsenic Nitrate FET technology
- Efficiency Level VI
- High Power Density: 12.5W/in³
- Smallest Footprint
- With 250kHz Switching Frequency
- SCP, OVP, OCP, and OTP
- 1-year warranty
- Dimensions C6 & C14: 161x54x33mm
- Dimensions C8: 150x54x33mm



*Product images are for illustrative purposes only and may vary from actual design.

■ Application

- Industrial Grade equipment

■ Model List

Custom Designs Available!

Model	Output Voltage	Output Current	Power
DT200AG-120-X-XX*	12V	16A	192W
DT200AG-180-X-XX*	18V	11.1A	200W
DT200AG-190-X-XX*	19V	10.5A	200W
DT200AG-191-X-XX*	19.5V	10.2A	200W
DT200AG-200-X-XX*	20V	10A	200W
DT200AG-240-X-XX*	24V	8.3A	200W
DT200AG-480-X-XX	48V	4.2A	200W
DT200AG-560-X-XX	56V	3.6A	200W

*Add -MX for 6-Pin Power Type Molex Output connector

■ Technical Data

Voltage	100-240Vac
Line Frequency	50-60Hz
Input Current	2.4A Max.
Protection	Internal Primary Current Fuse, Inrush Limiting
Configuration	IEC60320/C6, C8, C14
Load Regulation	±5% (Typical)
Ripple	1% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Topology	LLC
Over Voltage Protection	V out *120-150% Max.
Short Circuit Protection	Shut down

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

January 15, 2020

1 / 3

■ Technical Data(cont.)


Over Current Protection	I out *120-150% Max.
Over Temperature Protection	Latch Protection
DC Cord	UL2095/UL2464/16AWG/18AWG
Ferrite Core	Yes(Optional)
Dielectric Withstand	3000Vac Primary-Secondary
Leakage Current	0.25mA@ 2Pin/ 3.5mA@3Pin
Efficiency	95% Energy Star Level VI, ErP Stage 2 Certified, CoC Tier 2, NRCan & GEMS Certified
MTBF	300,000 calculated hours at 25°C, by Telcordia SR-332
Operating Temperature	0 to + 40°C
Storage Temperature	-20 to 80 °C
Relative Humidity Operating:	20 to 80% RH
Relative Humidity Storage	10 to 90% RH
Cooling	Natural Convection Cooling
Case Dimension C6 & C14	161x54x33mm
Case Dimension C8	150x54x33mm
Weight	560g
Molex Plug	6-Pin Housing Molex 39-01-2060 Connector or similar
Material Flammability	UL94V-0

Note: When Over Current Protection is activated, the power supply will shut down automatically. Once the abnormal condition resulting in the failure being removed, the power supply will restart. When Over Voltage Protection or Over Temperature Protection is activated, the power supply will latch.


■ Safeties/EMI

Safety Standard	IEC62368-1, IEC 60950-1
EMC Standards	EN55032
	EN61000-3-2,3
	EN55024

■ DC Output Cable Mechanical Diagram



*Molex 39-01-2060 Connector or similar for models with an output current of 5A and above.





Output Cable Plug Pin Assignment

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

January 15, 2020



***Some Safety Agency Approvals may differ from what is shown. Contact Autec Sales!**

***Product images are for illustrative purposes only and may vary from actual design.**

***Specifications are subject to change without notice. Autec is not responsible for issues arising from errors or omissions.**

Technical Sales / Customer Service: +1-818-338-7788 • Email: sales@autec.com

31328 Via Colinas Suite 102 • Westlake Village, CA 91362 USA • www.autec.com

January 15, 2020