

daA2500-60mci (S-Mount) – Tray (40pcs) - Basler dart

The Basler daA2500-60mci (S-Mount) BCON for MIPI camera module with the ON Semiconductor AR0521 CMOS sensor delivers 60 frames per second at 5 MP resolution. This model comes with a S-mount.



Number

Add to watch list

Specifications

General Information

Design-In Sample:	09/2019
Order Number	108009

Sensor

Sensor Vendor	ON Semiconductor
Sensor	AR0521
Shutter	Rolling Shutter
Max. Image Circle	1/2.5"
Sensor Type	CMOS
Resolution (HxV)	2560 px x 1920 px
Resolution	5 MP
Pixel Size (H x V)	2.2 μm x 2.2 μm
Frame Rate	60 fps
Mono/Color	Color

Camera Data

Interface	BCON for MIPI
Pixel Bit Depth	8, 12 bits
Synchronization	<ul style="list-style-type: none"> ▪ free-run ▪ software trigger
Image Processing	In-Camera Processing
Exposure Control	<ul style="list-style-type: none"> ▪ programmable via the camera API ▪ automatic ▪ manual

Camera Data

Digital Input	2
Digital Output	2
Power Requirements	▪ 5V DC (via BCON for MIPI interface)
Power Consumption (typical)	0.6 W

Housing

Housing Type	Board Level
Housing Size (L x W x H)	27 mm x 27 mm x 5.3 mm
Lens Mount	▪ S-mount
Weight (typical)	9g

Conformity

Conformity	<ul style="list-style-type: none">▪ RoHS▪ CE▪ FCC▪ GenICam▪ MIPI CSI-2▪ UL▪ KC
------------	--



eNewsletter

Regular updates on events and product innovations:



Basler on the social networks

Keep in touch with us via the social networks:

