

Products > Cameras > Area Scan Cameras > Basler dart

daA1920-160uc (No-Mount) - Basler dart

The Basler daA1920-160uc (No-Mount) USB 3.0 camera with the Sony IMX392 CMOS sensor delivers 160 frames per second at 2.3 MP resolution. This model has no mount.















Specifications

General Information

Design-In Sample:	now	
Series Production:	now	
Order Number	108232	
Ready for shipment Delivery times may vary. Please ask for the current availability and use the request cart.	approx. 14 days	
Destination	United States	▼

Sensor

Sensor Vendor	Sony
Sensor	IMX392
Shutter	Global Shutter
Max. Image Circle	1/2.3"
Sensor Type	CMOS
Sensor Size	6.6 mm x 4.2 mm
Resolution (HxV)	1920 px x 1200 px
Resolution	2.3 MP
Pixel Size (H x V)	3.45 µm x 3.45 µm
Frame Rate	160 fps
Mono/Color	Color

Camera Data

Interface	USB 3.0
B: 18:0	8, 12 bits

Camera Data Synchronization software trigger hardware trigger free-run Image Processing In-Camera Processing Exposure Control ■ programmable via the camera API ■ hardware trigger Digital Input 1 Digital Output General Purpose I/O 2 ■ Via USB 3.0 interface Power Supply Power Requirements 2 W (typical) Housing Housing Type Board Level Housing Size (L x W x H) 8 mm x 27 mm x 27 mm Lens Mount none Operating Temperature 0 - 50°C

5g

Weight (typical)

Conformity

Conformity

RoHS

USB3 Vision

CE

GenlCam

KC

UL

FCC

EAC



eNewsletter

Regular updates on events and product innovations:



Basler on the social networks

Keep in touch with us via the social networks:









