

Products > Cameras > Area Scan Cameras > Basler dart

daA3840-45um (No-Mount) - Basler dart

The Basler daA3840-45um (No-Mount) USB 3.0 camera with the Sony IMX334 CMOS sensor delivers 45 frames per second at 8.3 MP resolution. This model has no mount.







Specifications

General Information

	0	
Order Number	108270	
Series Production:	February 2021	
Design-In Sample:	now	

Sensor

Sensor Vendor	Sony
Sensor	IMX334
Shutter	Rolling Shutter
Max. Image Circle	1/1.8"
Sensor Type	CMOS
Sensor Size	7.7 mm x 4.3 mm
Resolution (HxV)	3840 px x 2160 px
Resolution	8.3 MP
Pixel Size (H x V)	2 µm x 2 µm
Frame Rate	45 fps
Mono/Color	Mono

Camera Data

Interface	USB 3.0
Pixel Bit Depth	8, 12 bits
Synchronization	 software trigger

Camera Data

		hardware triggerfree-run	
	Image Processing	In-Camera Processing	
	Exposure Control	programmable via the camera APIhardware trigger	
	Digital Input	1	
	Digital Output	2	
	General Purpose I/O	2	
	Power Supply	 Via USB 3.0 interface 	
	Power Requirements (typical)	1.8 W	
Housing			
	Housing Type	Board Level	
	Housing Size (L x W x H)	7.9 mm x 27 mm x 27 mm	
	Lens Mount	none	
	Operating Temperature	0 - 50°C	
	Weight (typical)	5g	
Conformity			
	Conformity	RoHSUSB3 VisionCE	
		 GenlCam 	
		KCUL	
		■ FCC	
		■ EAC	
f share	y tweet	in share mail	i
			-
			Basler on the social networks
Newsletter		Regular updates on events and product innovations:	
Newsletter Regular updates on events	and product innovations:		Keep in touch with us via the social netwo

© 2021 Basler AG Glossary Sitemap Legal Info Privacy Statement Legal Notice Terms and Conditions Contact Driving Directions 沪ICP备17041046号-1