

TECHNICAL SPECIFICATIONS

9416-2006/9416-2006S



Voltage	125	Plug  Receptacle 
Amperage	20	
VA per Input	2500 (20 x 125)	
Frequency	50/60 Hz	
Over Current Protection	20 AMP Thermal Breaker	
Switch	With Switch	
Indicators – LED(s)	1	
Power Cable Wire Gauge	12/3	
Power Cable Length	10 ft	
Plug Type	NEMA 5-20P Straight Blade	
Receptacle/Socket Type	NEMA 5-20R	
Quantity on Face	20	
Style	Duplex	
Maximum Output per Receptacle/Socket	20A	
Voltage per Receptacle/Socket	125	
Joule Rating	720	
UL 1449 Rating (500 Amps)	330 Volts	
Clamping Level	<315 Volts	
Response Time	<5 nanoseconds	
Technology Use	Super MOVs	
Surge Indicator Red LED	Yes	
Heavy Steel - Black Powder Coat	Yes	
Made in the USA	Yes	
Configuration	66" Vertical Rackmount	
Certification/Agency Approvals	UL & c-UL Listed 60950	
Certification/Agency Approvals	RoHS Compliant	
Chassis Dimensions (HxWxD)	66.25" x 1.85" x 1.30"	
Unit Weight	13	