

TECHNICAL SPECIFICATIONS

9416-3001/9416-3001S



Voltage	250	Plug  Receptacle (C-13)  Receptacle (C-19) 
Amperage	30	
VA per Input	7500 (30 x 250)	
Frequency	50/60 Hz	
Over Current Protection	(2) 20 AMP Double Pole Magnetic Breakers	
Switch	Breaker/Switch Combination	
Power Cable Wire Gauge	10/3	
Power Cable Length	10 ft	
Plug Type	NEMA L6-30P Twistlock Plug	
Combined Total Receptacle/Sockets	30	
Receptacle/Socket Type	IEC C-13	
Quantity on Face	24	
Quantity per Breaker	12	
Style	Banks of 4	
Maximum Output per Receptacle/Socket	15A per receptacle Bank	
Voltage per Receptacle/Socket	250	
Receptacle/Socket Type	IEC C-19	
Quantity on Face	6	
Quantity per Breaker	3	
Style	Individual	
Maximum Output per Receptacle/Socket	20A	
Voltage per Receptacle/Socket	250	
Heavy Steel - Black Powder Coat	Yes	
Made in the USA	Yes	
Configuration	66" Vertical Rackmount	
Certification/Agency Approvals	UL & c-UL Listed 60950	
Certification/Agency Approvals	FCC Part 15 Class A Conformance	
Certification/Agency Approvals	RoHS Compliant	
Chassis Dimensions (HxWxD)	66.25" x 2.0" x 3.5" (1.44" doghouse)	
Unit Weight	17	
Monitoring	Current Meter Local & Remote (Ethernet-EM) Digital RMS Scrolling Current Meter & Ethernet Connection for Remote Monitoring/Alarms/SNMP Traps +/-2% Accuracy with Full Scale 60Hz sine wave input	
Ethernet Connection	RJ45	