



Product: <u>943662080</u> ☑

24 V DC DIN rail power supply unit

Product Description 24 V DC DIN rail power supply unit

Technical Specifications

Product description

Туре:	RPS 80 EEC
Description:	24 V DC DIN rail power supply unit
Part Number:	943662080
More Interfaces	
Voltage input:	1 x Bi-stable, quick-connect spring clamp terminals, 3-pin
Voltage output:	1 x Bi-stable, quick-connect spring clamp terminals, 4-pin
Power requirements	
Current consumption:	max. 1.8-1.0 A at 100-240 V AC; max. 0.85 - 0.3 A at 110-125 V DC
Input voltage:	100-240 V AC (+/-15%); 50-60Hz or; 110-125 V DC (-20/+25%)
Operating Voltage:	230 V
Output current:	3.4-3.0 A continuous; min 5.0-4.5 A for typ. 4 sec
Redundancy functions:	Power supply units can be connected in parallel
Activation Current:	13 A at 230 V AC
Power Output	
Output voltage:	24 - 28 V DC (typ. 24.1 V) external adjustable
Output voltage:	24 - 28 V DC (typ. 24.1 V) external adjustable
	24 - 28 V DC (typ. 24.1 V) external adjustable LED (DC OK, Overload)
Software Diagnostics:	
Software Diagnostics:	
Software Diagnostics: Ambient conditions	LED (DC OK, Overload)
Software Diagnostics: Ambient conditions Operating temperature:	LED (DC OK, Overload) -25-+70 °C
Software Diagnostics: Ambient conditions Operating temperature: Note: Storage/transport temperature:	LED (DC OK, Overload) -25-+70 °C from 60 °C derating
Software Diagnostics: Ambient conditions Operating temperature: Note:	LED (DC OK, Overload) -25-+70 °C from 60 °C derating -40-+85 °C
Software Diagnostics: Ambient conditions Operating temperature: Note: Storage/transport temperature: Relative humidity (non-condensing):	LED (DC OK, Overload) -25-+70 °C from 60 °C derating -40-+85 °C
Software Diagnostics: Ambient conditions Operating temperature: Note: Storage/transport temperature: Relative humidity (non-condensing): Mechanical construction	LED (DC OK, Overload) -25-+70 °C from 60 °C derating -40-+85 °C 5-95 %

Mechanical stability

Mounting:

Protection class:

IEC 60068-2-6 vibration:	Operating: 2 500Hz 0,5m ² /s ³
IEC 60068-2-27 shock:	10 g, 11 ms duration

DIN Rail

IP20

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD):	± 4 kV contact discharge; ± 8 kV air discharge
EN 61000-4-3 electromagnetic field:	10 V/m (80 MHz 2700 MHz)
EN 61000-4-4 fast transients (burst):	2 kV power line
EN 61000-4-5 surge voltage:	power lines: 2 kV (line/earth), 1 kV (line/line)
EN 61000-4-6 Conducted Immunity:	10 V (150 kHz 80 MHz)

EMC emitted immunity

EN 55032:	EN 55032 Class A
Approvals	

Basis Standard:	CE
Safety of industrial control equipment:	cUL 60950-1, cUL 508
Safety of information technology equipment:	cUL 60950-1
Shipbuilding:	DNV

Reliability

Guarantee:	24 months (please refer to the terms of guarantee for detailed information)	

Scope of delivery and accessories

Soono	of delivery:
Scope	of delivery:

Scope of delivery:	Rail power supply, Description and operating manual
Further Instructions	
Product Documentation:	https://www.doc.hirschmann.com
Certificates:	https://www.doc.hirschmann.com/certificates.html
History	

Revision Number: 0.122 Revision Date: 04-17-2024

Update and Revision:

Variants

Item #	Туре
943662080	RPS 80 EEC

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.