




ПІН ISO 5456-2

Product description

Description	appliance plug
Type	GSP-U 3000 LO ..
Order No	832-954-..., see standard products
Number of contacts	3 + PE
Conductor size	max. 1,5 mm ²
Standard	DIN EN 175301-803
Construction type	A

Technical data

Rated voltage	400V AC/DC
Rated current *	16 A ; notice derating
Rated impulse voltage	6,0 kV
Pollution degree	3
Type of connection	solder

Materials

Contact	CuZn
Contact plating	see standard products
Contact bearer	PA 66 GF

Environmental conditions

Protection class (IEC 60529) *	IP65 *
Temperature range (connector)	-40°C to +125°C, notice derating

* unplugged and plugged. Plugged only if mounted and locked and in combination with Hirschmann connector

Flammability class

Contact bearer	UL 94 V-0
----------------	-----------

Packaging


Packaging unit	see standard products
----------------	-----------------------

Accessories

Mating connectors / fitting to	cable socket series: GDM..., GDML..., GDME...
--------------------------------	---

Cutline

Do not connect or disconnect under load.



Standard products

Artikel-No.	Type	Contact plating	Packaging unit
832-954-200	GSP-U 3000 LO SN	Cu/Sn	1000
832-954-400	GSP-U 3000 LO AU	Cu/Au	1000