



SPECIFICATION FOR ULTRASONIC SENSOR

TOTAL PAGE

09

www.bestarsensor.com

ROHS

Customer		Model Name	BPU1640T/ROAH12
Customer P/N		Product No.	100912
Date	31. Jul. 2012	Issue No.	BS/TEU01.330A
Page	01 of 09	Issue Date	2012/07/31

Approval:

- 1.Applications
- 2.Features
- 3.Technical terms
- 4.Drawing
- 5.Beam Pattern
- 6.Test Circuit
- 7.Reliability Test
- 8.Caution
- 9.Caution in use
- 10.Note
- 11.Packing
- 12.History change record

Drawn by	Checked by	Approved by	Customer approved
倪雪晴	邹东平	李红元	

BESTAR SENSORTECH CO.,LTD

Room 706.No.178. YuLong South Road,Zhonglou district,ChangZhou,
JiangSuProvince,P.R.China

Tel: +86 519 88990131 **Fax:** +86 519 88990133

E-mail:li@bestarsensor.com **<http://www.bestarsensor.com>**

BPU1640T/ROAH12

1.Applications

Burglar alarms 、 Range finds 、 Automatic doors 、 Remote control.



2. Features

- 2.1) Open Structure and fission
- 2.2) Compact and light weight.
- 2.3) High sensitivity and sound pressure.
- 2.4) Less power consumption.
- 2.5) High reliability


3.Technical terms

No.	Item	Unit	Specification	
1.	Type		BPU1640TOAH12	BPU1640ROAH12
2.	Construction		Open Structure	
3.	Using Method		Transmitter	Receiver
4.	Frequency	KHz	40±1K Hz	39±1K Hz
5.	Sound Pressure Level	dB	min.110dB (10V/30cm)	---
6.	Sensitivity	dB	---	min. -65dB /V/ μbar
7.	Capacitance	pF	2500pF±25% at 1KHz	
8.	Directivity	°	50deg	
9.	Operating Tem.Range	°C	-35 to +85 °C	
10.	Storage Tem.Range	°C	-35 to +85 °C	
11.	Detectable Range	m	0.7...18m	
12.	Allowable Input Voltage	Vp-p	60Vp-p	
13.	Housing Material		Aluminum	

				Date:	2012.07.31	BPU1640T/ROAH12
				Drawn by:	倪雪晴	
A	2012.07.31	倪雪晴		Checked by:	邹东平	Ultrasonic Sensor
Rev.	Date	Drawn	Note	Approved by:	李红元	
BESTAR SENSORTECH CO.,LTD						DRG NO: BS/TEU01.330A
www.bestarsensor.com li@bestarsensor.com						Page:2 of 9

BPU1640T/ROAH12

4.Drawing





unit:mm

A				Date:	2012.07.31	BPU1640T/ROAH12
				Drawn by:	倪雪晴	
	A	2012.07.31	倪雪晴	Checked by:	邹东平	Ultrasonic Sensor
	Rev.	Date	Drawn	Approved by:	李红元	
BESTAR SENSORTECH CO.,LTD						DRG NO: BS/TEU01.330A
www.bestarsensor.com li@bestarsensor.com						Page:3 of 9


BPU1640T/ROAH12

5. Beam Pattern




				Date:	2012.07.31	BPU1640T/ROAH12
				Drawn by:	倪雪晴	
A	2012.07.31	倪雪晴		Checked by:	邹东平	Ultrasonic Sensor
Rev.	Date	Drawn	Note	Approved by:	李红元	
BESTAR SENSORTECH CO.,LTD						DRG NO: BS/TEU01.330A
www.bestarsensor.com li@bestarsensor.com						Page:4 of 9

BPU1640T/ROAH12



Directivity in Overall Sensitivity

6.Test Circuit



R: 3.9K Ω Rc=1k Ω

T.G. :Target
F.G. :Function Generator
O.S. :Oscilloscope

				Date:	2012.07.31	BPU1640T/ROAH12
				Drawn by:	倪雪晴	
A	2012.07.31	倪雪晴		Checked by:	邹东平	Ultrasonic Sensor
Rev.	Date	Drawn	Note	Approved by:	李红元	
BESTAR SENSORTECH CO.,LTD						DRG NO: BS/TEU01.330A
www.bestarsensor.com li@bestarsensor.com						Page:5 of 9

BPU1640T/ROAH12

7. Reliability Test

- 7.1 High temp.life test
 Temperature +85±3 °C
 Duration 72hrs
- 7.2 Low temp.life test
 Temperature -40±3 °C
 Duration 72hrs
- 7.3 Heat Cycle Test
 Temperature +85±3 °C 1hour
 -40±3 °C 1hour
 Cycles 10cycles
- 7.4 Humidity Test
 Temperature +60±2 °C
 Relative Humidity 90~95%
 Duration 72hrs
- 7.5 Vibration Test
 Vibration Frequency 10~55Hz
 Sweep Period 1min
 Amplitude(peak to peak) 1.5mm
 Direction 3(x.y&z)
 Time 2hours/direction
- 7.6 Shock test
 Acceleration sine 100G
 Direction 3directions
 Shock time 3 time/directions
- 7.7 Drop test
 Height 1m on concrete floor
 Times 10times
- 7.8 Connector soldering check:
 Immersing terminal up to 1mm below base in soldering bath at 260 °C 10 seconds

Notice:

The variation of the S.P.L or the sensitivity at 40KHz is within 3dB compared with initial figures at 25 °C in 24 hours after above test condition.

				Date:	2012.07.31	BPU1640T/ROAH12
				Drawn by:	倪雪晴	
A	2012.07.31	倪雪晴		Checked by:	邹东平	Ultrasonic Sensor
Rev.	Date	Drawn	Note	Approved by:	李红元	
BESTAR SENSORTECH CO.,LTD						DRG NO: BS/TEU01.330A
www.bestarsensor.com li@bestarsensor.com						Page:6 of 9

BPU1640T/ROAH12

8. Caution

8.1 Limitation of Applications

Please contact us before using our product for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.

- 1) Aircraft equipment
- 2) Aerospace equipment
- 3) Undersea equipment
- 4) Power plant control equipment
- 5) Medical equipment
- 6) Transportation equipment (vehicles, train, ships, etc.)
- 7) Traffic signal equipment
- 8) Disaster prevention/crime prevention equipment
- 9) Data-processing equipment
- 10) Application of similar complexity and/or reliability requirement to the applications listed in the above

8.2 Fail -safe

Be sure to provide an appropriate fail-sate function on your product to prevent a second damage that may be caused by the abnormal function or the failure of our product

9. Caution in use

- 1) Please avoid applying an excessive stress to the transducer because it might be damaged.
- 2) The transducer may generate surge voltage by mechanical or thermal shock. Care should be taken to protect from it in designing your application circuit.
- 3) Please do not applying DC voltage to the transducer.
- 4) Please do not use the transducer in water.
- 5) The piece of sensor may be damaged by force pressure from back of sensor.
- 6) Please do not use the sensor without painting on the surface.
- 7) Please well evaluate the painting and electrical characteristic for your coating.


10. Note

- 1) Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
- 2) You are requested not to use our product deviating from the agreed specifications.
- 3) We consider it not to appropriate to include any terms and conditions with regard to the business transaction in the product specifications, drawings or other technical documents. Therefore, of your technical documents as above include such terms and conditions such as warranty clause, product liability clause, or intellectual property infringement liability clause, they will be deemed to be invalid

				Date:	2012.07.31	BPU1640T/ROAH12
				Drawn by:	倪雪晴	
A	2012.07.31	倪雪晴		Checked by:	邹东平	Ultrasonic Sensor
Rev.	Date	Drawn	Note	Approved by:	李红元	
BESTAR SENSORTECH CO.,LTD						DRG NO: BS/TEU01.330A
www.bestarsensor.com li@bestarsensor.com						Page:7 of 9

BPU1640T/ROAH12

11.Packing



- 1)50 pcs/tray
- 2)40 trays/carton
- 3)2000 pcs/carton in total
- 4)carton size: 500X280X340m m

A				Date:	2012.07.31	BPU1640T/ROAH12
				Drawn by:	倪雪晴	
	A	2012.07.31	倪雪晴	Checked by:	邹东平	Ultrasonic Sensor
	Rev.	Date	Drawn	Approved by:	李红元	
BESTAR SENSORTech CO.,LTD						DRG NO: BS/TEU01.330A
www.bestarsensor.com li@bestarsensor.com						Page:8 of 9

12. History change record

[illegible]

				Date:	2012.07.31	BPU1640T/ROAH12	
				Drawn by:	倪雪晴		
A	2012.07.31	倪雪晴		Checked by:	邹东平	Ultrasonic Sensor	
Rev.	Date	Drawn	Note	Approved by:	李红元		
BESTAR SENSORTECH CO.,LTD						DRG NO: BS/TEU01.330A	Page:9 of 9
www.bestarsensor.com li@bestarsensor.com							
6	5	4	3	2	1		