

# BP-2423N

24V / 2.3 Ah

- Battery pack for eNSP3-450P series
- Maintenance-free lead battery
- "Plug and Play" installation in 5.25" drive slot

The BP-2423N batterypack feeds UPS PC power supply units of the eNSP3-450P-xx series with energy. Very compact, it is intended to be installed into a 5.25" drive slot.

The connection between the batterypack and the UPS PC power supply unit is made through a connector equipped with a protection fuse. The lead batteries are free of maintenance.



## Technical data

Voltage	24 VDC
Capacitance	2.3 Ah
Number of batteries	2
Type of battery	Maintenance-free lead battery, 12 V
Backup time of a typical PC	300 W app. 2 minutes, 150 W app. 6 minutes
Fuse	30 A
Connector	JST, VL series
Operating temperature	0...+40 °C
Storage temperature	-20...+50 °C
Dimensions (WxDxH)	145 x 191 x 41,5 mm ±0.5mm
Weight (net)	2.7 kg

## Drawing BP-2423N

BATT PIN No.	Function
1	Batt +
2	N.C.
3	Batt -

Replace only by trained service people.  
 Danger of explosion if battery is incorrectly replaced!  
 Keep away from open flame. Danger of explosion!  
 Charge and discharge only in horizontal position.  
 During storage the battery pack should be recharged  
 every 6 months.

