



Features

- Wide 4 : 1 Input Voltage Range(9~36V,18~75V)
- Remote On/Off
- Input / Output Isolation Voltage: 1.5K Vdc
- Extended Operating Temperature Range: -40°C to +85°C
- Output Short Circuit Protection:
Continuous & Auto Recovery
- Over Voltage Protection: Clamp Mode
- Meet EN55022, Class A (Radiation)
- Shielded Metal Case with Insulated Baseplate
- Lead Free Design, RoHS Compliant
- 24pin DIP Package with Industry-Standard Footprint
- Customer Design Available



Description

The BOB5W Series are isolated 5W DC/DC converters. Designed with highly efficiency, allow the operating temperature range of these units to be -40°C to +85°C in a 24 pin DIP package with industry-standard footprint. Further features include wide 4 : 1 input voltage range, remote on/off control, short-circuit protection and over voltage protection.

Applications

These converters are well suitable for battery operated equipment, measurement equipment, telecom, wireless network, Industry control system, everywhere where isolated, tightly regulated voltages and compact size are required.

Technical Specification

All specifications are typical at nominal input, full load and 25°C unless otherwise stated.

Model Number	Input Voltage Range	Output Voltage (Vdc)	Output Current (mA)		Input Current (mA)		Eff. ⁽²⁾ (%)	Capacitive Load, max. ⁽³⁾ (uF)
			Min. Load ⁽¹⁾	Full. Load	No Load	Full Load		
BOB5-24S0W	9~36V Nominal:24Vdc	3.3	34	1200	4.6	226	77	6800
BOB5-24S1W		5	4	1000	9.7	274	80	7030
BOB5-24S2W		12	0	500	7.1	316	83	1220
BOB5-24S3W		15	0	400	10	321	82	430
BOB5-24D1W		±5	0	±500	9.2	271	81	4620
BOB5-24D2W		±12	0	±250	11.7	316	83	330
BOB5-24D3W		±15	0	±200	13	316	83	200
BOB5-48S0W	18~75V Nominal:48Vdc	3.3	49.4	1200	2.8	116	75	4400
BOB5-48S1W		5	0	1000	4.9	139	79	5460
BOB5-48S2W		12	0	500	5	160	82	660
BOB5-48S3W		15	0	400	5.2	160	82	330
BOB5-48D1W		±5	0	±500	5.4	139	79	1660
BOB5-48D2W		±12	0	±250	6.8	160	82	220
BOB5-48D3W		±15	0	±200	7.4	160	82	147


Input Specifications

Input Voltage	24V nominal input	9-36Vdc
	48V nominal input	18-75Vdc
Input filter		Pi Type
Input surge voltage (100ms max.)	24V input	50Vdc
	48V input	100Vdc
Input reflected ripple current	Nominal Vin and full load	160mA _{p-p} typ.
Start up time	Nominal Vin and constant resistive load	530ms typ.
Remote ON/OFF	Converter: ON	Open or $3.5V < V_r < 12V$
	Converter: OFF	Short ⁽⁴⁾ or $0V < V_r < 1.2V$
Sourcing current of remote control pin	Nominal Vin	< 0.2 mA
Idle input current (at Remote OFF state)	Nominal Vin	< 2.5 mA

Environmental Specifications

Operating ambient temperature	-40°C to +85°C (with derating)	
Maximum case temperature	+100°C	
Storage temperature range	-55°C to +105°C	
Relative humidity	5% to 95% RH	
Temperature coefficient	±0.02% / °C max.	

EMC Characteristics

EMI	EN55022 (radiation)	Meet class A
-----	---------------------	--------------

Output Specifications

Output power	6 Watts max.	
Voltage accuracy	Full load and nominal Vin	±2%
Minimum load	See table	
Line regulation	LL to HL at full load	±0.5%
	25% load to full load	Single ±1%
	Balanced load	Dual ±1%
Load Regulation	Unbalanced load 25% to 100% full load	±5%
Ripple and Noise	20MHz bandwidth	80mV _{p-p} max.
	3.3V _{out} models	3.9V
Over voltage protection (Zener Diode Clamp)	5V _{out} models	6.2V
	12V _{out} models	15V
	15V _{out} models	18V
Capacitive load	See table	
Over load protection	% of full load at nominal input	150% typ.
Short circuit protection	Continuous, automatic recovery	
Transient response settling time	50% load step change	560μs typ.
Transient response over shoot	di/dt=0.8A/μs	≤ ±5% of Vo




General Specifications

Efficiency	Nominal input	See table
Isolation voltage	Input to output	1500Vdc
Isolation resistance	500Vdc	10^9 Ohms min.
Isolation capacitance		300pF typ.
Switching frequency		300kHz typ.
Reliability, calculated MTBF		2.40×10^6 Hrs


Physical Specifications

Case material	Nickel-coated copper
Base material	Non-conductive black plastic
Potting material	Silicon rubber (UL94V-0)
Dimensions	$1.25 \times 0.80 \times 0.40$ Inch ($31.75 \times 20.32 \times 10.16$ mm)
Weight	17.2g (0.59oz) typ.


BOB5W Series
Power Derating Curve(5)





BOB5-48S1W
Input voltage vs. Efficiency




BOB5-48S1W
Output Current vs. Efficiency




BOB5-48S1W
Transient Response at 50%~100% Max Load

BOB5-48S1W
Loop Gain & Phase at Vi=48V, Full Load

Note

1. Io below this value will not damage these converters, however, they may not meet all listed specifications.
2. Typical value, tested at nominal input and full load.
3. For each output.
4. Short to -Vin (Pin 2,3).
5. Based on BOB5-48S1W.

Mechanical Dimensions


Unit: mm [inch]
Tolerance: ±0.5 [0.02]

Pin Assignment		
Pin	Single	Dual
1	Remote On/Off	Remote On/Off
2	-Vin	-Vin
3	-Vin	-Vin
9	No pin	Common
11	No function	-Vout
14	+Vout	+Vout
16	-Vout	Common
22	+Vin	+Vin
23	+Vin	+Vin

Specifications subject to change without notice.