




Features

- * Universal Input Range 85~264VAC
- * Efficiency to 79%
- * Meets EN55032 Class B
- * Continuous Short Circuit Protection
- * Low Leakage Current 0.25mA Max.
- * PCB Mountable



MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT(A)		RIPPLE (mVp-p) NOTE 1	VOLTAGE ACCURACY NOTE 2	LINE REGULATION NOTE 3	LOAD REGULATION NOTE 4	% EFF. (Typ.) NOTE 5
		MIN.	MAX.					
CFM05S033	3.3V	0A	1.25A	50mV	±1%	±0.5%	±1%	69%
CFM05S050	5.0V	0A	1.0A	50mV	±1%	±0.5%	±1%	73%
CFM05S090	9.0V	0A	0.55A	90mV	±1%	±0.5%	±1%	77%
CFM05S120	12.0V	0A	0.42A	120mV	±1%	±0.5%	±1%	77%
CFM05S150	15.0V	0A	0.33A	150mV	±1%	±0.5%	±1%	78%
CFM05S180	18.0V	0A	0.28A	180mV	±1%	±0.5%	±1%	79%
CFM05S240	24.0V	0A	0.23A	240mV	±1%	±0.5%	±1%	76%

Specifications are subject to change without notice.

Specifications

INPUT SPECIFICATIONS:

Voltage	85~264Vac 120~370Vdc
Frequency	47 to 63Hz
Inrush Current	40A max. @240Vac
Conducted EMI	CISPR/FCC Class B
Leakage Current	0.25mA max.


OUTPUT SPECIFICATIONS:

Holdup Time	8mS typ. @115Vac
Short Circuit Protection	Continuous (Auto Recovery)
Over Voltage Protection	TVS Component to Clamp
Temperature Coefficient	$\pm 0.05\%/^{\circ}\text{C}$ max.

GENERAL SPECIFICATIONS:

Isolation	Input to Output = 4,242VDC
Operating Temperature	0°C~ 85°C (See Derating Curve)
Storage Temperature	-20~85°C
Humidity	93% RH max. Non Condensing
Cooling	Natural Convection
Switching Frequency	60KHz Typical
MTBF	MIL-HDBK-217F. GB. at 25°C/115VAC 200Khrs min.
Altitude	2000m
Dimensions	2.165x1.378x0.827inches (55.00x35.00x21.00mm)
Weight	35g (0.08 Pounds)

CFM05S Series Derating Curve




SAFETY AND EMC:

Emission and Immunity	EN55032 Class B, EN61000-6-3 EN61000-3-2, EN61000-3-3, EN55024 EN61204-3, EN61000-6-1
Safety	IEC/UL 60950-1

NOTE:

1. Add a 0.1uF ceramic capacitor and a 10uF E.L. capacitor to output for Ripple & Noise measuring @20MHz BW.
2. Voltage accuracy is set at 100% rated load and 25°C Ta.
3. Line regulation is measured from 100Vac to 240Vac with full load.
4. Load regulation is measured from 10% to 100% full load.
5. Typical efficiency at 230VAC and full load at 25°C.

Mechanical Specification



Typical at 25°C, nominal line and 75% load, unless otherwise Specified