


Output Plug
and Polarity
are Dependent
on Customer
Requirements

General Specifications

- Input: 100~240Vac/ 50~60Hz
- Output: +12VDC/0~3000mA Regulated
- DC Cord: 5 FT, 18 AWG
- Operating/Storage Temperature: 0°C ~+40°C/ -20°C~+80°C
- Operating/Storage Humidity: 5%~90%RH
- Approvals: UL/CUL/FCC/LPS/WEEE/ROHS/VI
- Meets Energy Efficiency Level VI Standards
- Protection: Over Voltage/Short Circuit
- Packaged Unit Weight: .40 lb
- Carton Quantity: 50 pcs

Inner Box Dimensions:



135 x 70 x 55mm

ITEM NO.	S-12V0-3A0-U30	PART TITLE	Energy Efficient 12VDC / 3A North American Input Power Supply
PART NO.	S6-123A0W	 CONDOR ELECTRONICS, INC. T: 408-745-7141 F: 408-745-0439 990 San Antonio Road Palo Alto, CA 94303 USA sales@condorelectronics.net	
DATE	09.20.2016		
APPROVAL	TN		
UNIT	mm		
REV	0		

Safety Standards

Type(Marking)	Country/Region	Standard
UL/CUL	USA/Canada	Safety: UL 60950-1 2 nd edition
		Safety: CSA C22.2 No 60950-1-07
FCC	USA	EMI: FCC Part 15, Subpart B, Class B



**QUESTIONS ABOUT ANY OF CONDOR'S PRODUCTS PLEASE CALL/EMAIL TEL: 408-745-7141 / EMAIL: SALES@CONDORELECTRONICS.NET*