



Model	Output Voltage	Output Current		Max Power	Regulation	Ripple & Noise* (Vpp)
		Minimum	Maximum			
VPF-S800-12R	12 - 15 V	0 A	62.5 A	750 W	+/- 1%	1%
VPF-S800-18R	16 - 21 V	0 A	50 A	800 W	+/- 1%	1%
VPF-S800-24R	22 - 30 V	0 A	36.36 A	800 W	+/- 1%	1%
VPF-S800-36R	31 - 47 V	0 A	25.8 A	800 W	+/- 1%	1%
VPF-S800-48R	48 - 56 V	0 A	16.66 A	800 W	+/- 1%	1%

Input

Parameter	Conditions/Description	Min	Nom	Max	Units
Input Frequency		47		63	Hz
Input Voltage	At full range	180		264	VAC
Input Current	At 90 VAC full load			6	Amps
Inrush Current	Peak measured at 230 VAC and full load, cold start			70	Amps
PFC	Active power factor correction meets EN61000-3-2 class D				

Output

Parameter	Conditions/Description	Min	Nom	Max	Units
Transient response	Output voltage returns to within 1% in less than 2.5 mS for a 50 % load change and the peak transient does not exceed 5%.				
Overshoot	Turn-on and turn-off overshoot should not exceed 5% over nominal voltage.				
Efficiency	Measuring at 230 V and full load 12 V model: All other models:	80% 82%			
Turn on delay	At 120 VAC			1	second
Hold up time	At 120 VAC and 80% of rated maximim load	20			mS
Adjustability	Output user adjustable	+/- 5%			
Remote inhibit	Designated as RSW on the CN3. Requires a low signal to inhibit output.				
Remote sense	Designated as RS+ and RS- on the CN3. Total voltage compensation for cable losses with respect to the main output.				
LED display	Green - the power supply is operating normally. Orange - when any protection occurs or RSW is low.				
Power Good	Designated as PG on the CN3. This signal goes high 100-500 mS after the output reaches regulation. It goes low at least 1 mS before loss of regulation.				
Current sharing	Designated as CSH on the CN3. Connected with parallel units for forced current sharing and accuracy with up to 4 parallel units within 10% at full load.				
Current monitor	Designated as CMN on the CN3. CMN is a 0.5 V to 3 VDC output voltage to represent 1 to 100% output current.				
Output rating	Measured at output power connector (see chart above)				

* Output is fully isolated

* Ripple and noise is measured from 10 KHz to 20 MHz at output terminals with a 0.1 μ F ceramic capacitor and a 10 μ F electrolytic capacitor in parallel.



Protection Circuit

Parameter	Conditions/Description
Input circuit (primary)	Built-in ac fuse. A blown fuse indicates permanent damage to the power supply serviceable by factory only.
Input voltage protection	Power supply shut down when the ac input is under 80 VAC. When ac line reappears over 86 +/- 5 VAC, the power supply starts automatically.
Overpower protection	Current limiting starts at 110-140% of the rated output current and recovers automatically.
Short circuit protection	Short circuit can be continuous and recovers automatically.
Overvoltage protection	Output is protected against overvoltage. Unit shuts down and latches when voltage at output terminals exceeds 130% AC input needs to be reset to restart the power supply.
Over temp. protection	Power supply shuts down when temperature is in excess of 85 °C. Auto recovery.

Mechanical

Parameter	Conditions/Description	Min	Nom	Max	Units
Weight				1450	grams
Enclosure	98L X 4.33W X 2.5H				inches
Fan Drive	12 VDC/160 mA is available to drive an external fan				
Mounting inserts	4 Places 6-32 (see outline drawing for details)				

Mating Connector - Pin Header Version

Parameter	Conditions/Description
AC Input (CN1)	Mating Molex Part No. 09-91-0700 or equivalent (7 pin, 5 used)
Output (CN2)	Mating Molex Part No. 09-91-2000 (20 pin)
Output pin assignment	Molex: VO+ (Pins 1-10), VO- (Pins 11-20)

Mating Connector - Screw Terminal Version

Parameter	Conditions/Description
AC input (CN1)	Howder Terminal block Part No. HD-121-3P (3 pin)
Output (CN2)	Howder Terminal block Part No. HD-121-8P (8 pin)
Output pin assignment	Howder: VO+ (Pins 1-4), VO- (Pins 5-8)

Environmental

Parameter	Conditions/Description	Min	Nom	Max	Units
Operating temp.		0		50	°C
Storage temp.		-20		85	°C
Operating humid.	Non-condensing	5%		90%	RH
Storage humid.	Non-condensing	5%		95%	RH
Derating	Derates linearly from 100% load at 50 °C to 50% load at 70 °C.				

Safety and EMI

Parameter	Conditions/Description	Min	Nom	Max	Units
EMI requirement	Pass FCC Part 15 Subject J Class B, CISPR 22 class B				
Safety regulation	UL60950, CSA C22.2 No.. 950-95, TUV EN60950 and CB				
Leakage Current	When power supply is connected to a supply voltage equal to the upper limit of the rated voltage range.			3.5	mA
HI-POT	Applied for 3 seconds				
	Primary to secondary:	3000			VAC
	Primary to transformer core:	1500			VAC
	Primary to earth ground:	1500			VAC
Grounding Test	Allowable resistance measured when 25 A current is applied from the ground pin of the three prong plug to the far most earthed connection point.			0.1	Ohm

Reliability and MTBF

Parameter	Conditions/Description	Min	Nom	Max	Units
Warranty	Standard warranty length			2	years
MTBF	according to MIL-HBK-217 at 30 °C	150,000			hours

Burn in

Parameter	Conditions/Description	Min	Nom	Max	Units
Burn-in condition	Full load at 45 +/- 5 °C, 230 VAC.				
	Burn-in for up to 8 hours in early productions.				
	Time reduced gradually as product matures.				

