



OT LED25CV12EMD GE

97743

- LED 25W 12V, Dimmable
- Features & Benefits
 - Previous SKU: 901025012EMD
 - Dimmable 25W DC 12V constant voltage LED driver. Aluminum Casing. Potted.
 - Current: DC
 - Dimmable with Trailing Edge dimming
 - Designed for IP67
 - Reinforced insulation from input to output
 - High efficiency
 - PF: > 0.95Fully protected: Short circuit, Input voltage surge, Thermal, Secondary switch
 - Overload regulation, Over voltage protection. Self-resettable
 - AC/DCSoft start

Download PDF

Specifications

GENERAL CHARACTERISTICS

Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	75 °C
Storage Temperature	-10 °C
Color	Black
Primary Application	LED in- and outdoor lighting Street lighting Architectural lighting Sigge Indication and orientation lighting Ambience lighting
Product Technology	LED
CV/CC	CV
CC/CVvalue	12 V
Output Power (W)	25 W
Output Current (A)	2 A
Output Voltage[Nom]	12 V

ELECTRICAL CHARACTERISTICS

Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.25 A
Input Voltage Range[Min] (V)	0.15 A
Input Voltage Range[Max]	120 V
Input Current Range (Amperes)	240
Input voltage Range	V V

DIMENSIONS

Remote Mount Distance	140.0 m
Width	153.0 mm
Height	40.0 mm
Weight	30.5 mm

Products

- Indoor Fixtures
- Outdoor Fixtures
- Control and Sensors
- LED Lamps & Modules
- Refrigerated Display
- Signage
- See all Products

Resources

- Where to Buy
- Document Library
- My Account
- Pressroom
- The Institute
- Careers

Legal

- Privacy
- Terms
- Cookies

