

E-CATALOG > POWER SUPPLIES AND DRIVERS > LED DRIVERS > LED CONSTANT VOLTAGE DRIVERS > CONSTANT VOLTAGE LED > LED 25 DC 24

e-Catalog Search Enter Product Code or Description



OT#LED25CV24EPS GE

97526

- LED 25 DC 24
- Features & Benefits
 - Previous SKU: 901025024PS
 - LED 25 DC 24 - LED Driver, Constant Voltage, Aluminum Housing, Potted, with Leads, for Signage Applications
 - Current: DC
 - Designed for IP67
 - Reinforced insulation from input to output
 - Small form factor
 - Protections: Electronic internal Self-Resettable Short Circuit, Input Voltage Surge, Thermal
 - AC Input Fast Start-Up Time
 - 120-240V Input
 - High-efficiency

Download PDF

Specifications

GENERAL CHARACTERISTICS

Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	75 °C
Storage Temperature	-10 °C
Color	White
Primary Application	In-/Outdoor Signs Channel Lettering
Product Technology	LED
CV/CC	CV
CC/CVValue	24 V
Output Power (W)	25 W
Output Current (A)	1 A
Output Voltage[Nom]	24 V

ELECTRICAL CHARACTERISTICS

Power Factor %	Active
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.25 A
Input Voltage Range[Min] (V)	0.15 A
Input Voltage Range[Max]	120 V
Input Current Range (Amperes)	240
Input voltage Range	V V

DIMENSIONS

Remote Mount Distance	140.0 m
Width	153.0 mm
Height	40.0 mm
Weight	30.5 mm

Products

- Indoor Fixtures
- Outdoor Fixtures
- Control and Sensors
- LED Lamps & Modules
- Refrigerated Display
- Signage
- See all Products

Resources

- Where to Buy
- Document Library
- My Account
- Pressroom
- The Institute
- Careers

Legal

- Privacy
- Terms
- Cookies

© 2020
GE Current, a Daintree company

