

E-CATALOG > POWER SUPPLIES AND DRIVERS > LED DRIVERS > LED CONSTANT VOLTAGE DRIVERS > CONSTANT VOLTAGE LED > LED 60 DC 12

e-Catalog Search



OT LED60CV12EPS GE

97508

- LED 60 DC 12
- Features & Benefits**
- Previous SKU: 901060012PS
 - LED 60W DC 12V - LED Driver, Constant Voltage, Aluminum Housing, Potted, with Leads, For Signage applications
 - Current: DC
 - Designed for IP67
 - Reinforced insulation from input to output
 - Protections: Electronic internal Self-Resettable Short Circuit, Input Voltage Surge, Thermal
 - AC Input
 - Fast Start-Up Time 120-240V Input
 - High-efficiency

[Download PDF](#)

Specifications

GENERAL CHARACTERISTICS

Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	80 °C
Storage Temperature	-10 °C
Color	White
Primary Application	In-/Outdoor Signs Channel Lettering
Product Technology	LED
CV/CC	CV
CC/CVValue	12 V
Efficiency	0.85 %
Output Power (W)	60 W
Output Voltage[Nom]	12 V

ELECTRICAL CHARACTERISTICS

Power Factor %	Active
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.3 A
Input Voltage Range[Min] (V)	0.3 A
Input Voltage Range[Max]	220 V
Input Current Range (Amperes)	240
Input voltage Range	V V

Products

- ▶ Indoor Fixtures
- ▶ Outdoor Fixtures
- ▶ Control and Sensors
- ▶ LED Lamps & Modules
- ▶ Refrigerated Display
- ▶ Signage
- ▶ See all Products

Resources

- ▶ Where to Buy
- ▶ Document Library
- ▶ My Account
- ▶ Pressroom
- ▶ The Institute
- ▶ Careers

Legal

- ▶ Privacy
- ▶ Terms
- ▶ Cookies

© 2020
GE Current, a Daintree company

