

E-CATALOG > POWER SUPPLIES AND DRIVERS > LED DRIVERS > LED CONSTANT VOLTAGE DRIVERS > CONSTANT VOLTAGE LED > LED 60 DC 24

e-Catalog Search Enter Product Code or Description



OT LED60CV24EPS GE

97506

- LED 60 DC 24
- Features & Benefits
 - Previous SKU: 901060024PS
 - LED 60W DC 24V - LED Drive, Constant Voltage, Aluminum Housing, Potted, with Leads, for Signage Applications
 - Current: DC
 - Designed for IP67
 - Reinforced insulation from input to output
 - Protections: Electronic internal Self-Resettable Short Circuit, Input Voltage Surge, Thermal
 - AC Input
 - Fast Start-Up Time120-240V Input
 - High-efficiency

Download PDF

Specifications

GENERAL CHARACTERISTICS

Enclosure Type	Metal
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	80 °C
Storage Temperature	-10 °C
Color	White
Primary Application	In-/Outdoor Signs Channel Lettering
Product Technology	LED
Ripple (p-p)	2
CV/CC	CV
CC/CVvalue	24 V
Efficiency	0.85 %
Output Power (W)	60 W
Output Current (A)	2.5 A
Output Voltage[Nom]	24 V

ELECTRICAL CHARACTERISTICS

Power Factor %	Active
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.3 A
Input Voltage Range[Min] (V)	0.3 A
Input Voltage Range[Max]	220 V
Input Current Range (Amperes)	240
Input voltage Range	V V

DIMENSIONS

Width	198.0 mm
Height	44.0 mm
Weight	40.0 mm

Products

- Indoor Fixtures
- Outdoor Fixtures
- Control and Sensors
- LED Lamps & Modules
- Refrigerated Display
- Signage
- See all Products

Resources

- Where to Buy
- Document Library
- My Account
- Pressroom
- The Institute
- Careers

Legal

- Privacy
- Terms
- Cookies

© 2020 GE Current, a Daintree company



