CyberPower

CSB604 ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Essential Surge Protector CSB604 offers vital surge protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching your electronic equipment. The CSB604 provides 900 joules of protection with 6 outlets and a power cord (4 ft.).

Features of the CSB604 include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 900 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Plug style: Straight
- Outlet type: 6 NEMA 5-15R (surge-protected)
- Power cord: 4 ft
- Model style: Black
- EMI/RFI Filtration: Yes
- · Warranty: Limited lifetime
- Connected Equipment Guarantee: \$50,000



SPECIFICATIONS

| INPUT | | |
|-----------------------|----------------|--|
| Circuit Breaker | 15 A | |
| Cord Length | 4 ft (1.2 m) | |
| Input Plug Type | NEMA 5-15P | |
| Maximum Input Current | 15 A | |
| Plug Style | Straight | |
| OUTPUT | | |
| Outlet Type | 6 - NEMA 5-15R | |
| Outlets - Total | 6 | |

| SURGE PROTECTION & FILTERING | |
|------------------------------|---------------------------|
| Attenuation | 32 dB |
| Clamping Voltage | 500V (H-N, H-G, N-G) |
| Coax Protection RG6 | None |
| EMI/RFI Filtration | 150 KHz 100 MHz Yes |
| Maximum Surge Current | 45,000 A |
| Maximum Surge Current H-G | 15,000 A |
| Maximum Surge Current H-N | 15,000 A |
| Maximum Surge Current N-G | 15,000 A |
| Maximum Surge Voltage | 6,000 V |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 900 J |

CSB604 ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

| PHYSICAL | | |
|---|---|--|
| Color | Black | |
| Form Factors Supported | Keyhole (Wall Mount or Under-counter Installation) | |
| Keyhole Mounting Slots | Yes | |
| Material of Construction | Plastic | |
| PHYSICAL DIMENSIONS | | |
| Physical Dimensions - Width/Height/Depth (cm) | 4.45 x 3.81 x 24.77 cm | |
| Physical Dimensions - Width/Height/Depth (mm) | 44 x 38 x 248 mm | |
| Physical Dimensions - Width/Height/Depth (in.) | 1.75 x 1.5 x 9.75 in. | |
| Weight (kg) | 0.36 kg | |
| Weight (lb) | 0.8 lbs. | |
| SHIPPING DIMENSIONS | | |

| Weight (lb) | 0.8 lbs. | |
|---|---------------------------|--|
| SHIPPING DIMENSIONS | | |
| Shipping Dimensions - Width/Height/Depth (cm) | 5.72 x 33.02 x 13.34 cm | |
| Shipping Dimensions - Width/Height/Depth (mm) | 57.15 x 330.2 x 133.35 mm | |
| Shipping Dimensions - Width/Height/Depth (in.) | 2.25 x 13.0 x 5.25 in. | |
| Weight (kg) | 0.51 kg | |
| Weight (lb) | 1.13 lbs. | |
| | | |

| CERTIFICATIONS | | |
|----------------------------------|---------------------------|--|
| Environmental | RoHS Compliant | |
| Safety | UL 1363 | |
| WARRANTY | | |
| CEG Amount | \$50,000 | |
| Connected Equipment Guarantee | Lifetime | |
| Product Warranty | Limited Lifetime Warranty | |