



Basic Rack PDU



Basic Rack PDU includes horizontal, vertical, and toolless-mount varieties. Puts power where it is needed most - in the racks near the equipment. It Supply power from one branch whip to multiple pieces of ... [Full Description](#)

Dell Price **\$89.99**

[Add to Cart](#)

Usually Ships: in 1-3 days

[Free Shipping & Returns](#)

[Price Match](#)

[10% Back in Rewards*](#)

Manufacturer Part# : AP9562 | Dell Part# : A7247847

Overview

Tech Specs

Glossary And Resource

Tech Specs

Quick Specs

Device Type	Power distribution strip - rack-mountable
Cord Length	12 ft
Rack Size	19" - 1U
Weight	5.51 lbs
Input Voltage	AC 120 V
Output Voltage	AC 120 V
Power Capacity	1.8 kW
Input Connectors	1 x power NEMA 5-15
Output connectors	10 x power NEMA 5-15
Dimensions (WxDxH)	17.6 in x 2.2 in x 1.8 in
Manufacturer Warranty	2 years warranty
Designed For	P/N: AR3100, SU1400RMLB3U, SU1400RMLB3U-TRAD, SU1400RMLB3U-TU, SU2200RML3U-TU, SU3000RMNET-1EW, SU5000R5TBXFMR, SU5000R5TBXFMR-TU, SUA1000RM2U-TU, SUA1000RMUS, SUA1500R2X93-TU, SUA1500RMUS, SUA3000, SUA3000RM2U-TU, SUA750RMJ1UB, SUM3000RML2U, SUM3000RML2U-TU, SURTA3000XL, SURTA3000XL-TU

General

Device Type	Power distribution strip - rack-mountable
Height (Rack Units)	1U
Rack Size	19"
Cord Length	12 ft
Color	Black

Power Device

Input Voltage	AC 120 V
Input Voltage Range	AC 100 - 120 V
Input Connectors	1 x power NEMA 5-15
Power Output Connectors Details	10 x power NEMA 5-15
Output Voltage	AC 120 V
Max Electric Current	15 A
Power Capacity	1.8 kW
Circuit Protection	Circuit breaker

Miscellaneous

Cables Included	1 x power cable - integrated - 12 ft
-----------------	--------------------------------------

Rack Mounting Kit	Included
Compliant Standards	UL, cUL, UL 1363
Manufacturer Warranty	
Service & Support	- Limited warranty - parts and labor - 2 years - Limited warranty - replacement - 2 years
Environmental Parameters	
Min Operating Temperature	23 °F
Max Operating Temperature	113 °F
Min Storage Temperature	-13 °F
Max Storage Temperature	149 °F
Humidity Range Operating	0 - 95%
Humidity Range Storage	0 - 95%
Dimensions & Weight	
Width	17.6 in
Depth	2.2 in
Height	1.8 in
Weight	5.51 lbs
Compatibility Information	
Designed For	P/N: AR3100, SU1000R2BX120, SU1000RM, SU1000RM2U, SU1000RMNET, SU1400R2BX120, SU1400R2X122, SU1400RM, SU1400RM2U, SU1400RMBX120, SU1400RMNET, SU1400RMX176, SU1400RMXL3U, SU1400RMXLB3U, SU1400RMXLB3U-TRAD, SU1400RMXLB3U-TU, SU1400RMXLNET, SU1500RMX155, SU2000R3X155, SU2200R3BX120, SU2200R3X106, SU2200R3X147, SU2200R3X152, SU2200R3X152-TU, SU2200R3X167, SU2200RM, SU2200RM3U, SU2200RMNET, SU2200RMXL3U, SU2200RMXL3U-TU, SU2200RMXLNET, SU2200RMXLNET, SU2200RMXLTX153, SU3000R3BX120, SU3000R3BX135, SU3000R3X145, SU3000R3X145-TU, SU3000RM3U, SU3000RMJ3U, SU3000RMNET, SU3000RMNET-1EW, SU3000RMT3U, SU3000RMTX136, SU3000RMX93, SU3000RMXL3U, SU5000R5TBXFMR, SU5000R5TBXFMR-TU, SU5000RMT5U, SU5000RMT5U-TU, SU5000RMT5UXFMR, SU700R2BX120, SU700R2BX120-TU, SU700RM2U, SUA1000RM2U, SUA1000RM2U-TU, SUA1000RMUS, SUA1500R2X93-TU, SUA1500RMUS, SUA3000, SUA3000RM2U, SUA3000RM2U-TU, SUA750RM1U, SUA750RM2U, SUA750RM2U-TU, SUA750RMJ1UB, SUM3000RMXL2U, SUM3000RMXL2U-TU, SURTA3000XL, SURTA3000XL-TU

Do more with Dell

Employee and Student Discounts

PartnerDirect

Dell Outlet

TechCenter

Make a Payment

About Dell

Investors

Company Information

Corporate Social Responsibility

Customer Engagement

Careers

Dell Newsroom

Dell Technologies

Legal

Ads & Emails

Privacy Statement

Legal & Regulatory

Terms of Sale

Trademarks

Community

The Dell Community

Read Our Blog

Support Forums

Events

Offers subject to change, not combinable with all other offers. Taxes, shipping, handling and other fees apply. U.S. Dell Small Business new purchases only. LIMIT 5 DISCOUNTED OR PROMOTIONAL ITEMS PER CUSTOMER. Dell reserves right to cancel orders arising from pricing or other errors.