



DELL Smart UPS 1500RM



Smart-UPS is the most popular UPS in the world for servers, storage and network power protection. Trusted to protect critical data and equipment from power problems by supplying clean and reliable network-grade ... [Full Description](#)

Dell Price **\$749.99**

[Customize It](#)

[Add To Cart](#)

Usually Ships: in 1-3 days

[Free Shipping & Returns](#)

[Price Match](#)

[10% Back in Rewards*](#)

Manufacturer Part# : DLT1500RM2U | Dell Part# : A7545501

Overview

Tech Specs

Glossary And Resource

Tech Specs

Quick Specs

Device Type UPS - rack-mountable

Rack Size 2U

Weight 63.14 lbs

Input Voltage AC 120 V

Output Voltage AC 120 V

Power Capacity 1000 Watt / 1440 VA

Input Connectors Power NEMA 5-15

Output connectors 6 x power NEMA 5-15

Battery Lead acid

Battery Form Factor Internal

Batteries Qty 1

Run Time (Up To) 7 min at full load

Networking RS-232, USB

Dimensions (WxDxH) 17 in x 18 in x 3.5 in

Manufacturer Warranty 3 years warranty

General

Device Type UPS - rack-mountable

Battery Enclosure Type Internal

Height (Rack Units) 2U

Color Black

Power Device

UPS Technology Line interactive

Input Voltage AC 120 V

Input Voltage Range AC 82 - 144 V

Input Voltage Range (Adjustable) AC 75 - 154 V

Frequency Required 50/60 Hz

Input Connectors Power NEMA 5-15

Power Output Connectors Details 6 x power NEMA 5-15

Output Voltage AC 120 V

Power Capacity 1000 Watt / 1440 VA

Output Waveform Sinewave

Surge Suppression	Yes
Surge Energy Rating	459 Joules
Battery	
Quantity	1
Technology	Lead acid
Run Time (Up To)	7 min at full load 26 min at half load
Recharge Time	3 hours
Features	Maintenance free, leak proof
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (RS-232) 1 x management (USB) - 4 pin USB Type B
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	1 x power cable - 8 ft 1 x USB cable - external 1 x serial cable - external
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, LED indicators
Compliant Standards	FCC Class A certified, CSA, UL 1449, UL 1778, RoHS, REACH
Software / System Requirements	
Software Included	Drivers & Utilities
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	0 - 95%
Sound Emission	46 dBA
Dimensions & Weight	
Width	17 in
Depth	18 in
Height	3.5 in
Weight	63.14 lbs
Dimensions & Weight (Shipping)	
Shipping Width	23.4 in
Shipping Depth	23.7 in
Shipping Height	9.9 in
Shipping Weight	70.3 lbs

Do more with Dell

Employee and Student Discounts
PartnerDirect
Dell Outlet
TechCenter
Make a Payment

About Dell

Investors
Company Information
Corporate Social Responsibility
Customer Engagement
Careers
Dell Newsroom
Dell Technologies

Legal

Ads & Emails
Privacy Statement
Legal & Regulatory
Terms of Sale
Trademarks

Community

The Dell Community
Read Our Blog
Support Forums
Events

Offers subject to change, not combinable with all other offers. Taxes, shipping, handling and other fees apply. U.S. Dell Small Business new purchases only. LIMIT 5 DISCOUNTED OR PROMOTIONAL ITEMS PER CUSTOMER. Dell reserves right to cancel orders arising from pricing or other errors.