

LSE-9911

50 Watt COMBINED DATA AND POWER ADAPTER

The LSE-9911 is a combined data and power adapter that interfaces to the customer's wireless modem and other Link and Net outdoor products. The unit provides an RJ-45 input connector for connection to an IEEE 802.3 (10Base-T) compatible device. The unit receives power from 100V to 240V using an industry standard mating connector. An output terminal block provides the 10Base-T data and 24V or other voltages for connection to the wireless modem.

Main Features

- Option for easy installation on wall
- Compact size - 135 x 66 x 32 mm
- High efficiency - free convection cooling
- Wide-range input voltage covering worldwide requirements
- Full output protection OCP. SC. OVP
- Meets FCC 15 & EN55022 class B requirements
- Operating temperature range 0 °C to +40 °C with no derating
- Unit supplied with AC cord & DC filtered cable
- TUV, UL & CSA approved



Typical applications

- Fast data modems
- Wireless modems
- 10 base-T systems
- Video / Data / Voice modems

telkoor power supplies Ltd.

Natanya, Israel.
T 972-9-8632310,
F 972-9-8658444,
sales@telkoor.com
www.telkoor.com

Fremont, CA
T 510-657-2635,
F 510-657-6634,
telkoorsales@digipwr.com
www.digipwr.com

Salisbury, England
T 44 (0) 1722 413060,
F 44 (0) 1722 413034,
telkoorsales@greshampower.com
www.greshampower.com

Ordering Information

Model No .	Voltage	Current	R & N	Efficiency
LSE-9911-12	12- 5%	4.25	<300mVP-P@20Mhz	79%
LSE-9911-15	15- 5%	3.5	<300mVP-P@20Mhz	80%
LSE-9911-18	18- 5%	3.0	<300mVP-P@20Mhz	81%
LSE-9911-24	24- 5%	2.2	<300mVP-P@20Mhz	83%

Input

- 90 to 265VAC (wide range)
- Input frequency 47-63Hz
- Input inrush current 40A@ cold start
- Input reflected ripple per FCC part 15 & EN55022 class B
- Input cable 3 poles or 2 poles upon customer's request

Output

- Output voltage and current - See table above
- Voltage regulation - $\pm 2\%$ Max. For load and line variation
- Temperature coefficient - 0.05% / C max.
- Voltage set point - Internal trim-pot $\pm 5\%$
- Hold-up time - 9 mSec minimum at full load including 100V input
- Isolation - input/output, input/case >3000VAC
- Protection - output protected against overload, short-circuit and over-voltage
- Over-temperature protection - optional

Environmental

- Operation temperature range 0°C to +40°C
- Storage temperature range -10°C to +60°C
- EMI / RFI - Meets EN55022 class B requirements & IEC-1000 requirements
- MTBF - Higher than 200,000 hours
- Safety - EN-60950 UL-1950 CSA-22.2 and DENTORI

Mechanical

- Size - 135Lx66Wx32Hmm
- Weight - 200 g. max.
- Cooling - free convection
- Input AC - 2 pin or 3 AC inlet (cable included)
- Load connection - UL1185 18# filtered Jack connector