

Specifications

Photo is representative



Eaton 41-3261

Eaton E57 Series Tubular Metal Faced Inductive Proximity Sensor, Straight, Sensor dist: 2 mm, dist, 100 mA max DC, NO PNP Open Collector, 100 mA at 30 Vdc, 4 Pin M12 Connector, 10-30 Vdc input, < 1% accuracy, Short circuit protected, Shielded

General specifications

PRODUCT NAME	Eaton E57 inductive proximity sensor
CATALOG NUMBER	41-3261
UPC	782113967967
PRODUCT LENGTH/DEPTH	6.5 in
PRODUCT HEIGHT	0.31 in
PRODUCT WIDTH	4.5 in
PRODUCT WEIGHT	0.075 lb
WARRANTY	1 year
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Listed CSA Certified

Product specifications

CONTACT RATING	100 mA at 30 Vdc
OPERATING TEMPERATURE	-13° to 158°F (-25° to 70°C)
ACCURACY	< 1%
ENCLOSURE MATERIAL	Stainless steel
CONNECTION	4-pin M12 connector
PROTECTION	Short circuit protected
SENSOR TYPE	Inductive proximity
CONTACT CONFIGURATION	NO PNP open collector
ENVIRONMENTAL RATING	NEMA 4, NEMA 4X, NEMA 6P, NEMA 12, NEMA 13, IP67
INPUT VOLTAGE	10-30 Vdc
LED INDICATOR	Output status: red
MAXIMUM DC CURRENT	100 mA
OPERATING MODE	Shielded
SWITCH TYPE	Inductive proximity