Specifications

Photo is representative



Eaton E51ALS16P

Eaton E51 NEMA limit switch inductive proximity sensor, Modular Inductive **Proximity Sensor Enclosur** 500 mA AC/DC SS Output 8 Ft. (2.5m) Cable, 20-264Vac/DC input, < 0.3% accuracy, Shielded, 8 Ft.(2.4m), Side Sensing, 2-Wire AC, NO

General specifications

PRODUCT NAME

CATALOG

NUMBER **UPC**

PRODUCT

PRODUCT

PRODUCT

HEIGHT

WIDTH **PRODUCT**

WEIGHT WARRANTY

COMPLIANCES

CERTIFICATIONS

CATALOG NOTES

LENGTH/DEPTH

RATING	AC/Do Solid
ACTUATOR FUNCTION	Shield
CABLE TYPE	SOOV
ACCURACY	< 0.3%
ENCLOSURE MATERIAL	Recep and housin die cas zinc Head: plastic
CONNECTION	8 ft (2 m) cal
CONTACT CONFIGURATION	2-wire
SENSOR TYPE	Induct
	NEMA NEMA 3S, NEMA
ENVIRONMENTAL RATING	NEMA 4X,
	NEMA NEMA
	INEIVIA
	6P, NEM
	6P, NEMA 12, NEMA
CORD LENGTH	6P, NEMA 12,
OPERATING TEMPERATURE -	6P, NEMA 12, NEMA 13, IP
OPERATING TEMPERATURE - MAX	6P, NEMA 12, NEMA 13, IP
OPERATING TEMPERATURE -	6P, NEMA 12, NEMA 13, IP
OPERATING TEMPERATURE - MAX OPERATING TEMPERATURE -	6P, NEMA 12, NEMA 13, IP 96 ft
OPERATING TEMPERATURE - MAX OPERATING TEMPERATURE - MIN MAXIMUM AC	6P, NEMA 12, NEMA 13, IP 96 ft 158 °F
OPERATING TEMPERATURE - MAX OPERATING TEMPERATURE - MIN MAXIMUM AC CURRENT MAXIMUM DC	6P, NEMA 12, NEMA 13, IP 96 ft 158 °F -13 °F
OPERATING TEMPERATURE - MAX OPERATING TEMPERATURE - MIN MAXIMUM AC CURRENT MAXIMUM DC CURRENT	6P, NEMA 12, NEMA 13, IP 96 ft 158 °F -13 °F 500 m 500 m
	ENVIRONMENTAL

Product specifications

CONTACT