## **Specifications**

Photo is representative

## Eaton E51ALS520

**Product specifications** 

CONTACT

500 m

AC/D

Solid Outpu

Shield

< 0.39 Reception and housing

die ca

zinc Head: plastic Screw

termir

2-wire

Eaton E51 NEMA limit	CONTACT RATING
switch inductive proximity sensor, Modular Inductive	ACTUATOR FUNCTION
Proximity Sensor Enclosure,	ACCURACY
Side Sensing, Sensor dist 24 mm, 2-Wire AC, NO, 500 mA AC/DC SS Output, Screw Terminals, 20- 264Vac/DC input, < 0.3%	ENCLOSURE MATERIAL
accuracy, Shielded	CONNECTION

General specifications		CONFIGURATION	AC, N
General specific	Eaton E51	SENSOR TYPE	Induct proxin
PRODUCT NAME	NEMA limit switch inductive proximity sensor	ENVIRONMENTAL RATING	NEMA NEMA 3S, NEMA NEMA
CATALOG NUMBER	E51ALS520		4X, NEM/
UPC	782113881515		NEMA 6P,
PRODUCT LENGTH/DEPTH	1.54 in		NEM/ 12,
PRODUCT HEIGHT	4.53 in		NEMA 13, IP
PRODUCT WIDTH	1.78 in	OPERATING TEMPERATURE - MAX	158 °F
PRODUCT WEIGHT	0.9938 lb	OPERATING TEMPERATURE -	-13 °F
WARRANTY	1 year	MIN	
CERTIFICATIONS	UL Listed CSA Certified	MAXIMUM AC CURRENT	500 m
CATALOG NOTES Sensor head features a programmable output selector switch for NO or NC operation	features a programmable output selector switch for NO or NC	MAXIMUM DC CURRENT	500 m
		INPUT VOLTAGE	20-264 Vac/de
		LED INDICATOR	Power green Outpu status: yellow
	PROTECTION	Short circuit protec	

